

CAVITY DESIGN AND O-RING SELECTION FOR STATIC
SEAL USE IN AIRCRAFT TUBELESS TIRE WHEELS

Issued 11-15-63
Revised

1. PURPOSE:

The purpose of this Aerospace Standard is to establish design practices for aircraft tubeless tire wheel static seals.

2. SCOPE:

This standard applies to the cavity design and the selection of O-rings for tubeless tire wheels.

3. O-RING CAVITY DESIGN:

- 3.1 For use with 0.139 cross-section diameter O-ring, see Figure 1.
- 3.2 For use with 0.210 cross-section diameter O-ring, see Figure 1.
- 3.3 For use with 0.275 cross-section diameter O-ring, see Figure 1.
- 3.4 O-ring contact surfaces shall not exceed a maximum roughness of 63 RHR.

CAUTION

Care should be taken to prevent excessive and/or rough paint on O-ring contact surfaces which will prevent sealing.

- 3.5 Refer to MIL-P-5514 for static seal cavity design for use with demountable flange wheels.

4. O-RING SELECTION:

- 4.1 Material from MIL-P-25732 or MIL-P-5516 is recommended for use in this type seal.
- 4.2 O-ring stretch should be limited to 3 to 8 per cent of nominal ID in the installed position.
- 4.3 See ARP 568 for O-ring sizes and corresponding dash number.

THIS DOCUMENT SUPERCEDES AND CANCELS ARP 666, ISSUED 4-30-62.

Prepared by
SAE Committee A-5, Aircraft Wheels, Brakes, Skid Controls & Axles

Section 8.3 of the SAE Technical Board rules provides that: "All technical reports, including standards approved and practices recommended, are advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. There is no attempt to adhere to any SAE standard or recommended practice, and no commitment to conform to or be guided by any technical report. In formulating and approving technical reports, the Board and its Committees will not investigate or consider patents which may apply to the subject matter. Prospective users of the report are responsible for protecting themselves against liability for infringement of patents."