

Issued 1963-11
Revised 1982-05
Noncurrent 2005-01
Cancelled 2011-01

Superseding AS666C

**Cavity Design and O-ring Selection for Static Seal
Use in Aircraft Tubeless Tire Wheels**

RATIONALE

This document has not been maintained. The document's primary purpose was to provide instructions for designing a static seal gland and o-ring for the wheel halves. Modern wheel static seal gland & o-ring design must take into account the wheel size, use, environment and type (for example demountable flange). The designs depend on these factors such that the designs will vary for different applications as opposed to having one design for all applications as AS 666 specifies.

CANCELLATION NOTICE

This document has been declared "CANCELLED" as of January 2011. By this action, this document will remain listed in the Numerical Section of the Aerospace Standards Index.

SAENORM.COM : Click to view the full PDF of as666D

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2010 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS666D>**

NONCURRENT NOTICE

This specification has been declared "NONCURRENT" as of January 2005. It is recommended, therefore, that this document not be specified for new designs.

Each of these "NONCURRENT" documents is available from SAE.

Document made inactive for new designs. Committee feels that the practice amongst wheel manufacturers is to use proprietary gland standards and materials to improve seal integrity rendering this document obsolete for new design. This document shall be retained for historical record only.

SAENORM.COM : Click to view the full PDF of as666d

1. PURPOSE: This Aerospace Standard (AS) establishes design practices for aircraft tubeless tire wheel static seals.
2. SCOPE: This AS applies to the cavity design and the selection of O-rings for tubeless tire wheels.
3. O-RING CAVITY DESIGN:
 - 3.1 For use with 0.103 cross-section diameter O-ring, See Figure 1, page 3.
 - 3.2 For use with 0.139 cross-section diameter O-ring, See Figure 1, page 3.
 - 3.3 For use with 0.210 cross-section diameter O-ring, See Figure 1, page 3.
 - 3.4 For use with 0.275 cross-section diameter O-ring, See Figure 1, page 3.
 - 3.5 O-ring contact surfaces shall not exceed a maximum roughness of 63 RHR.

CAUTION

Care should be taken to prevent excessive and/or rough paint on O-ring contact surfaces which will prevent sealing.

- 3.6 Refer to MIL-P-5514 for static seal cavity design for use with demountable flange wheels.

4. O-RING SELECTION:

- 4.1 Material from MIL-P-25732 or MIL-P-5516 is recommended for use in this type seal.
- 4.2 O-ring stretch should be limited to 3 to 8 percent of nominal ID in the installed position.
- 4.3 See AS 568 for O-ring sizes and corresponding dash number.

SAENORM.COM : Click to view the full PDF of as666d

PREPARED BY
SUBCOMMITTEE A-5A, WHEELS, BRAKES & SKID CONTROLS OF COMMITTEE A-5,
AEROSPACE LANDING GEAR SYSTEMS