


SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. E	FEDERAL SUPPLY CLASS 5970	
	RATIONALE AS7928/6E IS BEING STABILIZED BECAUSE THE PROCESSES/PRODUCT IS CONSIDERED MATURE AND THE COMMITTEE DOES NOT ANTICIPATE FUTURE TECHNICAL CHANGES. STABILIZATION DOES NOT IMPLY THE PROCESS OR PRODUCT IS UNACCEPTABLE FOR APPLICATIONS FOR WHICH IT IS DESIGNED. ANY TECHNICAL CHANGES NOTED BY A SUPPLIER OR USER WHICH RESULTS IN A PRODUCT OR REQUIREMENT CHANGE WILL BE ADDRESSED BY A NEW REVISION. A QUALIFIED SUPPLIER IS STILL MAINTAINED. STABILIZED NOTICE THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE AE-8C2 TERMINATING DEVICES AND TOOLING COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.	
AS7928™/6	SAENORM.COM : Click to view the full PDF of as7928_6e	
For more information on this standard, visit https://www.sae.org/standards/content/AS7928/6E/		THIRD ANGLE PROJECTION 
CUSTODIAN: AE-8C2		PROCUREMENT SPECIFICATION: AS7928
	AEROSPACE STANDARD SPICES, CONDUCTOR, CRIMP STYLE, ELECTRIC (PERMANENT, TYPE II, CLASS 1) FOR 150 °C TOTAL CONDUCTOR TEMPERATURE	AS7928™/6
		REV. E




FIGURE 1 - AS7928/6 SPLICE

TABLE 1 - AS7928/6 DIMENSIONS

DASH NO.	WIRE RANGE	A MAX	BØ 1/	CØ 1/	D MIN	E	FØ 1/ MIN	G MIN	COLOR IDENTIFICATION
-1	26-24	.890 (22.6)	.033/.027 (0.84/0.69)	.160/.125 (4.07/3.18)	.060 (1.52)	.150/.125 (3.81/3.18)	.070 (1.78)	.025 (0.64)	YELLOW
-2	24-20	1.035 (26.29)	.055/.043 (1.40/1.09)	.170/.135 (4.32/3.43)	.060 (1.52)	.165/.135 (4.19/3.43)	.100 (2.54)	.030 (0.76)	WHITE
-3	22-18	1.300 (33.02)	.073/.052 (1.85/1.32)	.220/.160 (5.59/4.07)	.080 (2.03)	.210/.160 (5.33/4.07)	.110 (2.79)	.050 (1.27)	RED
-4	16-14	1.300 (33.02)	.095/.081 (2.41/2.06)	.260/.180 (6.60/4.57)	.080 (2.03)	.250/.180 (6.35/4.57)	.140 (3.56)	.050 (1.27)	BLUE
-5	12-10	1.700 (43.18)	.139/.129 (3.53/3.28)	.320/.250 (8.13/6.35)	.110 (2.79)	.300/.250 (7.62/6.35)	.200 (5.08)	.050 (1.27)	YELLOW

1/ DIAMETERS ARE THE SAME ON BOTH ENDS OF THE SPLICE.

REQUIREMENTS: ALL REQUIREMENTS SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS7928.

1. MIN CABLE INSULATION SUPPORT: .060 FOR DASH 1 AND 2
.094 FOR DASH 3, 4, AND 5
2. MATERIAL: COPPER (SEE ACQUISITION SPECIFICATION) OR COPPER ALLOY. MATERIAL SHALL HAVE ADEQUATE ELECTRICAL CONDUCTIVITY AND SHALL BE SUFFICIENTLY STRONG TO RESIST CRACKING AFTER FORMING AND CRIMPING.
3. INSULATING SLEEVE: REFER TO AS7928.
4. FINISH: METAL, TIN PLATED: REFER TO AS7928.
5. COLOR IDENTIFICATION: INSULATION SHALL BE THE NATURAL MATERIAL COLOR AND TRANSPARENT:
 - a. COLOR STRIPES: LONGITUDINAL COLOR STRIPES (2 OR MORE) .062 WIDE PER TABLE 1 SHALL BE ADDED UNDER THE INSULATION. STRIPES SHALL RUN THE LENGTH OF THE TUBE. THE STRIPES MUST EXTEND TO WITHIN 1/16 INCH OF THE ENDS OF THE INSULATION.
 - b. COLOR RINGS (OPTIONAL METHOD): A COLOR RING, .062 WIDE ON EACH END OF TUBE, PER TABLE 1 SHALL BE ADDED. THE RINGS MUST COVER A MINIMUM OF 315° OF THE CIRCUMFERENCE.
6. DIMENSIONS ARE IN INCHES AND SHALL BE AS SPECIFIED IN TABLE 1 AND FIGURE 1. DIMENSION B SHALL BE DETERMINED AS THE AVERAGE OF TWO DIAMETERS MEASURED IN TWO PLACES VERTICALLY AND HORIZONTALLY OR MEASURED IN TWO LOCATIONS 90° APART. METRIC UNITS SHOWN IN PARENTHESES IS BASED ON 25.4 MM PER INCH. IN THE EVENT OF A CONFLICT, ENGLISH UNITS TAKE PRECEDENCE.
7. THE INSPECTION WINDOW AND LOCATOR SHALL PROVIDE A POSITIVE MEANS OF POSITIONING SPLICE IN THE APPLICABLE CRIMPING TOOL AND PROVIDE VISIBLE INSPECTION OF STRIPPED WIRE ENDS.
8. CRIMPING TOOLS: CRIMPING TOOLS FOR THE AS7928/6 SPLICES SHALL BE AS SPECIFIED IN TABLE 2.

TABLE 2 - AS7928/6 CRIMP TOOLS

PART NUMBER	WIRE RANGE	CRIMP TOOL	TOOL DIE	DIE COLOR DESIGNATION
M7928/6-1	26-24	M22520/5-01	M22520/5-101	WHITE
		M22520/10-01	M22520/10-102	
M7928/6-2	24-20	M22520/5-01	M22520/5-101	
		M22520/10-01	M22520/10-102	
M7928/6-3	22-18	M22520/5-01	M22520/5-101 (WIRE SIZE 22-20 ONLY)	RED
		M22520/10-01	M22520/10-101	
M7928/6-4	16-14	M22520/5-01	M22520/5-107	BLUE
		M22520/10-01	M22520/10-101	WHITE
M7928/6-5	12-10	M22520/5-01	M22520/5-108	YELLOW
		M22520/10	M22520/10-100	
		M22520/41-01 FIX DIE TOOL	N/A	N/A

9. INSULATION SUPPORT AND WIRE METAL CRIMP SPLICE MAY BE MULTIPLE PIECE CONSTRUCTION. CONTOUR MAY VARY FROM THAT SHOWN, WITHIN SPECIFIED DIMENSIONS, BUT WIRE LEAD-IN TO WIRE BARREL SHALL BE PROVIDED.
10. FOR QUALIFICATION, SPLICES SHALL BE TESTED WITH AS22759/87 WIRE (SIZES 26 THROUGH 10) OR AN EQUIVALENT WIRE WITH AS29606 TYPE NCC SMALL DIAMETER NICKEL COATED COPPER CONDUCTOR.
11. FLATTENING OF INSULATION SLEEVE TO FORM LOCATOR MAY CAUSE THE SLEEVE TO EXCEED THE E DIMENSION BY .050 MAX IN THE LOCATOR AREA.
12. PART NUMBER: CONSISTS OF THE LETTER "M," THE BASIC NUMBER OF THIS SPECIFICATION SHEET, AND A DASH NUMBER SPECIFIED IN TABLE 1.

EXAMPLE: M7928/6-1 SPLICE FOR 26-24 WIRE RANGE.

	AEROSPACE STANDARD	AS7928™/6 SHEET 2 OF 3	REV. E
	SPLICES, CONDUCTOR, CRIMP STYLE, ELECTRIC (PERMANENT, TYPE II, CLASS 1) FOR 150 °C TOTAL CONDUCTOR TEMPERATURE		