

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

AS85049/11

FEDERAL SUPPLY CLASS
5935

NOTICE


THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-C-85049/11A AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-C-85049/11A. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

SAENORM.COM : Click to view the full PDF of as85049 - 11

THIRD ANGLE PROJECTION



ISSUED 2001-07

PREPARED BY SAE SUBCOMMITTEE AE-8C1

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space®
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL,
ENVIRONMENTAL, CABLE SEALING, STRAIGHT, CATEGORY 1A
(FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703
SERIES 3, AND MIL-C-83723 SERIES III CONNECTORS)

AS85049/11
SHEET 1 OF 22

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION: MIL-C-85049.




FIGURE 1. CONFIGURATION AND DIMENSIONS.

TABLE I. DIMENSIONS.

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6)		Style	B +.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Wire Bundle Accommodation Range					
						Min	Max				
01	3				4	.125	.250	1	2.00	1.027	.669
02									3.00		
03					6	.250	.437	2	2.75	1.027	.669
04									3.75		
05		8	8S	8	4	.125	.250	1	2.00	1.027	.617
06									3.00		
07					6	.250	.437	2	2.75	1.027	.617
08									3.75		
09		10	10S, 10SL	10	4	.125	.312	1	2.00	1.027	.734
10									3.00		
11					6	.250	.437	2	2.75	1.027	.734
12									3.75		
13	7	12	12, 12S	12	6	.250	.437	1	2.00	1.027	.858
14									3.00		
15					10	.350	.625	2	2.75	1.027	.858
16									3.75		
17	12	14	14, 14S	14	10	.350	.575	1	2.00	1.027	.984
18									3.00		
19					12	.500	.750	2	2.75	1.059	.984
20									3.75		

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL,
ENVIRONMENTAL, CABLE SEALING, STRAIGHT, CATEGORY 1A
(FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703
SERIES 3, AND MIL-C-83723 SERIES III CONNECTORS)

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	E Ref	V Thread Class 2A	F Dia Max	G Max	H Max
01	1.06	.625-24 UNEF	-	3.15	3.51
02	2.06			4.15	4.51
03	1.81	.750-20 UNEF	.858	3.90	4.26
04	2.81			4.90	5.26
05	1.06	.625-24 UNEF	-	3.15	3.51
06	2.06			4.15	4.51
07	1.81	.750-20 UNEF	.858	3.90	4.26
08	2.81			4.90	5.26
09	1.06	.625-24 UNEF	-	3.15	3.51
10	2.06			4.15	4.51
11	1.81	.750-20 UNEF	.858	3.90	4.26
12	2.81			4.90	5.26
13	1.06	.750-20 UNEF	-	3.15	3.51
14	2.06			4.15	4.51
15	1.67	1.000-20 UNEF	1.112	3.90	4.26
16	2.67			4.90	5.26
17	0.92	1.000-20 UNEF	-	3.15	3.51
18	1.92			4.15	4.51
19	1.67	1.1875-18 UNEF	1.218	3.93	4.29
20	2.67			4.93	5.29

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL,
ENVIRONMENTAL, CABLE SEALING, STRAIGHT, CATEGORY 1A
(FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703
SERIES 3, AND MIL-C-83723 SERIES III CONNECTORS)

AS85049/11
SHEET 4 OF 22

AS85049/11

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B +.125	C Ref	D Dia Max				
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max								
21	19	16	16,16S	16	12	.500	.700	1	2.00	1.059	1.112				
22									3.00						
23					16	.625	.937	2	2.75	1.156	1.112				
24									3.75						
25	27	18	18	18	10	.350	.625	1	2.00	1.027	1.218				
26									3.00						
27					12	.500	.750	1	2.00	1.059	1.218				
28									3.00						
29					16	.625	.937	2	2.75	1.156	1.218				
30									3.75						
31					37	20	20	20	10	.350	.625	1	3.00	1.027	1.345
32													4.00		
33	12	.500	.750	1					3.00	1.059	1.345				
34									4.00						
35	16	.625	.937	2					3.75	1.156	1.345				
36									4.75						
37	20	.875	1.250	2					3.75	1.375	1.345				
38									4.75						
39		22	22	22	10	.350	.625	1	3.00	1.027	1.468				
40									4.00						

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	E Ref	V Thread Class 2A	F Dia Max	G Max	H Max
21	0.92	1.1875-18 UNEF	-	3.18	3.54
22	1.92			4.18	4.54
23	1.67	1.4375-18 UNEF	1.468	4.02	4.38
24	2.67			5.02	5.38
25	0.92	1.000-20 UNEF	-	3.15	3.51
26	1.92			4.15	4.51
27	0.92	1.1875-18 UNEF	-	3.18	3.54
28	1.92			4.18	4.54
29	1.67	1.4375-18 UNEF	1.468	4.02	4.38
30	2.67			5.02	5.38
31	1.92	1.000-20 UNEF	-	4.15	4.51
32	2.92			5.15	5.51
33	1.92	1.1875-18 UNEF	-	4.18	4.54
34	2.92			5.18	5.54
35	2.67	1.4375-18 UNEF	1.468	5.02	5.38
36	3.67			6.02	6.38
37	2.67	1.750-18 UNS	1.969	5.24	5.60
38	3.67			6.24	6.60
39	1.92	1.000-20 UNEF	-	4.15	4.51
40	2.92			5.15	5.51

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL,
ENVIRONMENTAL, CABLE SEALING, STRAIGHT, CATEGORY 1A
(FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703
SERIES 3, AND MIL-C-83723 SERIES III CONNECTORS)

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B +.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max				
41		22	22	22	12	.500	.750	1	3.00	1.059	1.468
42					4.00						
43					16	.625	.937	1	3.00	1.156	1.468
44									4.00		
45					20	.875	1.250	2	3.75	1.375	1.468
46									4.75		
47		24	24	24	12	.500	.750	1	3.00	1.059	1.593
48					4.00						
49					16	.625	.812	1	3.00	1.156	1.593
50									4.00		
51					16	.625	.937	1	3.00	1.156	1.593
52									4.00		
53					20	.875	1.250	2	3.75	1.375	1.593
54									4.75		
55					12	.500	.750	1	3.00	1.059	1.969
56					4.00						
57					16	.625	.937	1	3.00	1.156	1.969
58									4.00		
59					20	.875	1.250	1	3.00	1.375	1.969
60									4.00		

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	E Ref	V Thread Class 2A	F Dia Max	G Max	H Max
41	1.92	1.1875-18 UNEF	-	4.18	4.54
42	2.92			5.18	5.54
43	1.92	1.4375-18 UNEF	-	4.27	4.63
44	2.92			5.27	5.63
45	2.67	1.750-18 UNS	1.969	5.24	5.60
46	3.67			6.24	6.60
47	1.92	1.1875-18 UNEF	-	4.18	4.54
48	2.92			5.18	5.54
49	1.92	1.4375-18 UNEF	-	4.27	4.63
50	2.92			5.27	5.63
51	1.92	1.4375-18 UNEF	-	4.27	4.63
52	2.92			5.27	5.63
53	2.67	1.750-18 UNS	1.969	5.24	5.60
54	3.67			6.24	6.60
55	1.92	1.1875-18 UNEF	-	4.16	4.68
56	2.92			5.16	5.68
57	1.92	1.4375-18 UNEF	-	4.26	4.78
58	2.92			5.26	5.78
59	1.92	1.750-18 UNS	-	4.48	5.00
60	2.92			5.48	6.00

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL,
ENVIRONMENTAL, CABLE SEALING, STRAIGHT, CATEGORY 1A
(FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703
SERIES 3, AND MIL-C-83723 SERIES III CONNECTORS)

AS85049/11
SHEET 8 OF 22

AS85049/11


TABLE I. DIMENSIONS (CONTINUED).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B +.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max				
61			28		24	1.000	1.375	1	3.00	1.500	1.969
62									4.00		
63					16	.625	.937	1	3.00	1.156	2.219
64									4.00		
65					20	.875	1.250	1	3.00	1.375	2.219
66			32						4.00		
67					24	1.000	1.375	1	3.00	1.500	2.219
68									4.00		
69					28	1.250	1.625	1	3.00	1.781	2.219
70									4.00		
71					20	.875	1.250	1	4.00	1.375	2.469
72									5.00		
73					24	1.000	1.375	1	4.00	1.500	2.469
74									5.00		
75			36		28	1.250	1.625	1	4.00	1.781	2.469
76									5.00		
77					32	1.437	1.875	2	4.88	1.830	2.469
78									5.88		
79			40		20	.875	1.250	1	4.00	1.375	2.719
80									5.00		

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	E Ref	V Thread Class 2A	F Dia Max	G Max	H Max
61	1.92	2.000-18 UNS	-	4.60	5.12
62	2.92			5.60	6.12
63	1.92	1.4375-18 UNEF	-	4.26	4.78
64	2.92			5.26	5.78
65	1.92	1.750-18 UNS	-	4.48	5.00
66	2.92			5.48	6.00
67	1.92	2.000-18 UNS	-	4.60	5.12
68	2.92			5.60	6.12
69	1.92	2.250-16 UN	-	4.89	5.41
70	2.92			5.89	6.41
71	2.92	1.750-18 UNS	-	5.49	6.01
72	3.92			6.49	7.01
73	2.92	2.000-18 UNS	-	5.60	6.12
74	3.92			6.60	7.12
75	2.92	2.250-16 UN	-	5.89	6.41
76	3.92			6.89	7.41
77	3.80	2.500-16 UN	2.719	6.81	7.33
78	4.80			7.81	8.33
79	2.92	1.750-18 UNS	-	5.48	6.00
80	3.92			6.48	7.00

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B	C	D Dia														
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		+ .125	Ref		Max																
										Min	Max														
81						24	1.000	1.375	1	4.00	1.500	2.719													
82										5.00															
83										40			28	1.250	1.625	1	4.00	1.781	2.719						
84																	5.00								
85																	32			1.437	1.875	1	4.00	1.830	2.719
86																							5.00		
87										44			20	.875	1.250	1	4.00	1.375	2.969						
88																	5.00								
89																	24			1.000	1.375	1	4.00	1.500	2.969
90																							5.00		
91										48			28	1.250	1.625	1	4.00	1.781	2.969						
92																	5.00								
93																	32			1.437	1.875	1	4.00	1.830	2.969
94																							5.00		
95													20	.875	1.250	1	4.00	1.375	3.219						
96																	5.00								
97																	24			1.000	1.375	1	4.00	1.500	3.219
98																							5.00		
99													28	1.250	1.625	1	4.00	1.781	3.219						
100																	5.00								

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL,
ENVIRONMENTAL, CABLE SEALING, STRAIGHT, CATEGORY 1A
(FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703
SERIES 3, AND MIL-C-83723 SERIES III CONNECTORS)

AS85049/11

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	E Ref	V Thread Class 2A	F Dia Max	G Max	H Max
81	2.92	2.000-18 UNS	-	5.60	6.12
82	3.92			6.60	7.12
83	2.92	2.250-16 UN	-	5.89	6.41
84	3.92			6.89	7.41
85	2.92	2.500-16 UN	-	5.93	6.45
86	3.92			6.93	7.45
87	2.92	1.750-18 UNS	-	5.48	6.00
88	3.92			6.48	7.00
89	2.92	2.000-18 UNS	-	5.60	6.12
90	3.92			6.60	7.12
91	2.92	2.250-16 UN	-	5.89	6.41
92	3.92			6.89	7.41
93	2.92	2.500-16 UN	-	5.93	6.45
94	3.92			6.93	7.45
95	2.92	1.750-18 UNS	-	5.48	6.00
96	3.92			6.48	7.00
97	2.92	2.000-18 UNS	-	5.60	6.12
98	3.92			6.60	7.12
99	2.92	2.250-16 UN	-	5.89	6.41
100	3.92			6.89	7.41

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B +.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max				
101			48		32	1.437	1.875	1	4.00	1.830	3.219
102									5.00		
103	61				12	.500	.750	1	3.00	1.059	1.653
104									4.00		
105					16	.625	.937	1	3.00	1.156	1.653
106									4.00		
107					20	.875	1.250	2	3.75	1.375	1.653
108									4.75		
109					24	1.000	1.375	2	3.75	1.500	1.653
110									4.75		
111	7	12	12,12S	12	10	.350	.500	1	2.00	1.027	.858
112	19	16	16,16S	16	6	.250	.437	1	2.00	1.027	1.112
113									3.00		
114	7	12	12,12S	12	4	.125	.312	1	2.00	1.027	.858
115									3.00		
116	12	14	14,14S	14	6	.250	.437	1	2.00	1.027	.984
117									3.00		
118	19	16	16,16S	16	10	.350	.625	1	2.00	1.027	1.112
119									3.00		

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	E Ref	V Thread Class 2A	F Dia Max	G Max	H Max
101	2.92	2.500-16 UN	-	5.93	6.45
102	3.92			6.93	7.45
103	1.92	1.1875-18 UNEF	-	4.18	4.54
104	2.92			5.18	5.54
105	1.92	1.4375-18 UNEF	-	4.27	4.63
106	2.92			5.27	5.63
107	2.67	1.750-18 UNS	1.969	5.24	5.60
108	3.67			6.24	6.60
109	2.67	2.000-18 UNS	1.969	5.37	5.73
110	3.67			6.37	6.73
111	1.00	1.000-20 UNEF	-	3.15	3.51
112	1.00	.750-20 UNEF	-	3.15	3.51
113	2.00			4.15	4.51
114	1.00	.625-24 UNEF	-	3.15	3.51
115	2.00			4.15	4.51
116	1.00	.750-20 UNEF	-	3.15	3.51
117	2.00			4.15	4.51
118	0.92	1.000-20 UNEF	-	3.15	3.51
119	1.92			4.15	4.51

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL,
ENVIRONMENTAL, CABLE SEALING, STRAIGHT, CATEGORY 1A
(FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703
SERIES 3, AND MIL-C-83723 SERIES III CONNECTORS)

AS85049/11
SHEET 14 OF 22

AS85049/11

TABLE I. DIMENSIONS (CONTINUED).



Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B ±.125	C Ref	D Dia Max
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max				
120	27	18	18	18	4	.125	.312	1	2.00	1.027	1.218
121									3.00		
122					6	.250	.437	1	2.00	1.027	1.218
123									3.00		
124	37	20	20	20	6	.250	.437	1	3.00	1.027	1.345
125									4.00		
126		22	22	22	4	.125	.312	1	3.00	1.027	1.468
127									4.00		
128					6	.250	.437	1	3.00	1.027	1.468
129									4.00		
130		24	24	24	10	.350	.625	1	3.00	1.027	1.593
131									4.00		
132			36		12	.500	.750	1	4.00	1.059	2.469
133									5.00		
134			40		12	.500	.750	1	4.00	1.059	2.719
135									5.00		
136		10	10S, 10SL	10	6	.250	.375	1	2.00	1.027	.734
137									3.00		
138	7	12	12, 12S	12	10	.350	.500	1	2.00	1.027	.858
139									3.00		

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	E Ref	V Thread Class 2A	F Dia Max	G Max	H Max
120	0.92	.625-24 UNEF	-	3.15	3.51
121	1.92			4.15	4.51
122	0.92	.750-20 UNEF	-	3.15	3.51
123	1.92			4.15	4.51
124	1.92	.750-20 UNEF	-	4.15	4.51
125	2.92			5.15	5.51
126	1.92	.625-24 UNEF	-	4.15	4.51
127	2.92			5.15	5.51
128	1.92	.750-20 UNEF	-	4.15	4.51
129	2.92			5.15	5.51
130	1.92	1.000-20 UNEF	-	4.15	4.51
131	2.92			5.15	5.51
132	2.92	1.1875-18 UNEF	-	5.32	5.68
133	3.92			6.32	6.68
134	2.92	1.1875-18 UNEF	-	5.16	5.68
135	3.92			6.16	6.68
136	1.06	.750-20 UNEF	-	3.15	3.51
137	2.06			4.15	4.51
138	1.06	1.000-20 UNEF	-	3.15	3.51
139	2.06			4.15	4.51

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL,
ENVIRONMENTAL, CABLE SEALING, STRAIGHT, CATEGORY 1A
(FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703
SERIES 3, AND MIL-C-83723 SERIES III CONNECTORS)

AS85049/11
SHEET 16 OF 22

AS85049/11

TABLE I. DIMENSIONS (CONTINUED).

Dash No.	Fits Shell of Connector				Clamp Size	A (see note 6) Wire Bundle Accommodation Range		Style	B +.125	C Ref	D Dia Max	
	MIL-C-81703 Ser 3	MIL-C-26482 Ser 2	MIL-C-5015 Crimp	MIL-C-83723 Ser III		Min	Max					
140	37	20	20	20	18	.625	.904	1	3.00	1.156	1.345	
141									4.00			
142		22	22	22	20	.875	1.029	1	3.00	1.375	1.468	
143									4.00			
144		24	24	24	20	.875	1.144	1	3.00	1.375	1.593	
145									4.00			
146			36		32	1.437	1.840	1	4.00	1.830	2.469	
147									5.00			
148					18	.625	.937	1	4.00	1.156	2.469	
149									5.00			
150	12	14	14,14S	14	4	.125	.312	1	2.00	1.027	.984	
151									3.00			
152	19	16	16,16S	16	4	.125	.312	1	2.00	1.027	1.112	
153									3.00			
154			44		16	.625	.937	1	4.00	1.156	2.969	
155									5.00			
156			40		16	.625	.937	1	4.00	1.156	2.719	
157									5.00			