

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

AS85049/41

FEDERAL SUPPLY CLASS
5935

NOTICE


THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-C-85049/41A AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-C-85049/41A. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

SAENORM.COM : Click to view the full PDF of as85049 - 41

THIRD ANGLE PROJECTION



ISSUED 2001-07

PREPARED BY SAE SUBCOMMITTEE AE-8C1

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL,
NONENVIRONMENTAL, STRAIN RELIEF, STRAIGHT,
CATEGORY 4C (FOR MIL-C-5015 SOLDER TYPE, V THREAD
OF MS310X CLASSES A, B, C OR K CONNECTORS)

AS85049/41
SHEET 1 OF 5

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION: MIL-C-85049.

AS85049/41

INACTIVE FOR NEW DESIGN EQUIPMENT OR
MODIFICATION OF EXISTING EQUIPMENT,
USE MIL-C-85049/42.




FIGURE 1. CONFIGURATION AND DIMENSIONS.

TABLE I. DIMENSIONS.

Dash No.	Connector Shell Size (Ref) See Note 7	A Thread	B Wire Bundle Accommodation Max	C	D	E $\pm .031$ Dia	F $\pm .031$	G $\pm .031$	Bushing (Ref) See Note 8
-3A	8S & 10S	.500-28 UNEF-2B	.250	.047	.406	.688	.812	.812	MS3420-3
-4A	10SL, 12S & 12	.625-24 UNEF-2B	.312	.062		.812	.875		MS3420-4
-6A	14S & 14	.750-20 UNEF-2B	.438	.078		.969	1.062	.875	MS3420-6
-8A	16S & 16	.875-20 UNEF-2B	.562	.109		1.094	1.156	.938	MS3420-8
-10A	18	1.000-20 UNEF-2B	.625	.125		1.188	1.250		MS3420-10
-12A	20 & 22	1.188-18 UNEF-2B	.750	.156		1.375	1.469		MS3420-12
-16A	24 & 28	1.438-18 UNEF-2B	.938	.188		1.656	1.688	1.031	MS3420-16
-20A	32	1.750-18 UNS-2B	1.250	.250	.469	2.031	2.031	1.094	MS3420-20
-24A	36	2.000-18 UNS-2B	1.375	.297	.531	2.219	2.281	1.156	MS3420-24
-28A	40	2.250-16 UN-2B	1.625	.328		2.500	2.688	1.688	MS3420-28
-32A	44	2.500-16 UN-2B	1.875	.375	.594	2.781	2.938	1.750	MS3420-32
-40A	48	3.000-16 UN-2B	2.375	.453	.656	3.281	3.500		MS3420-40

Dash No.	Fillister Head Screw				Screw Size	MS35338 Washer, Lock Dash Number
	AN500D Dash Number	MS35275 Dash Number	AN501D Dash Number	MS25276 Dash Number		
-3A	4-7	216			4-40	135
-4A	4-10	218			4-40	135
-6A	6-12	232			6-32	136
-8A	6-12	232			6-32	136
-10A	6-14	248			6-32	136
-12A	8-16	249			8-32	137
-16A	8-18	N/A			8-32	137
-20A	8-24	251			8-32	137
-24A	416-28	286	10-24	269	10-32	138
-28A					1/4-20	139
-32A					1/4-20	139
-40A					1/4-20	139

N/A = Not Available

INCH	mm	INCH	mm	INCH	mm
0.016	0.41	0.453	11.51	1.250	31.75
0.020	0.51	0.469	11.91	1.375	34.93
0.031	0.79	0.500	12.70	1.438	36.53
0.032	0.81	0.531	13.49	1.469	37.31
0.047	1.19	0.562	14.27	1.625	41.28
0.062	1.57	0.594	15.09	1.688	42.88
0.078	1.98	0.625	15.88	1.750	44.45
0.109	2.77	0.656	16.66	1.875	47.63
0.125	3.18	0.750	19.05	2.000	50.80
0.156	3.96	0.812	20.62	2.031	51.59
0.188	4.78	0.875	22.22	2.250	57.15
0.250	6.35	0.938	23.83	2.281	57.94
0.297	7.54	1.000	25.40	2.375	60.32
0.312	7.92	1.031	26.19	2.500	63.50
0.328	8.33	1.062	26.97	2.688	68.28
0.375	9.53	1.094	27.79	2.938	74.63
0.406	10.31	1.156	29.36	3.000	76.20
0.438	11.13	1.188	30.18	3.500	88.90

REQUIREMENTS:

- Design and construction:
Dimensions and configuration: See figure 1.
- Material and finish: See table II.

TABLE II. MATERIAL AND FINISH.

Material	Finish
Aluminum alloy in accordance with MIL-C-85049	<u>1</u> / W

1/ W finish is not for use in space application.

- Qualification: See MIL-C-85049, category 4C, examination of product, salt spray and post examination, only tests required.
Information pertaining to qualification of products may be obtained from the Commanding Officer, Naval Avionics Center, Attention: Code B/444, 6000 East 21st Street, Indianapolis, IN 46219-2189.
- Part number: See example below:

M85049/
41
-3A

Military designator _____
 Specification sheet _____
 Dash number (see table I) _____