

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.


REV.
A

AS85052/1

FEDERAL SUPPLY CLASS
5340


RATIONALE

AS85052/1A HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.



SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS85052/1A>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3E

PROCUREMENT SPECIFICATION: AS85052 /5/



AEROSPACE STANDARD

(R) CLAMP, LOOP, TUBE, 17-7PH, 275 °F,
FUEL AND PETROLEUM BASED
HYDRAULIC FLUID RESISTANT

AS85052/1
SHEET 1 OF 3

REV.
A

TABLE 1 - CLAMP DIMENSIONS

BASIC NO. AS85052/1 SIZE CODE /13/	TUBE SIZE	(C)	ØD	E ±.032	(J)	R RAD ±.010	T TOLERANCE PER AMS2242	(Y)
-02	.125	.192	.125	.468	—	.090	.020	.325
-03	.188	.224	.188	.499	—	.090	.020	.325
-04	.250	.255	.250	.530	.235	.090	.020	.325
-05	.312	.286	.312	.561	.235	.090	.020	.325
-06	.375	.318	.375	.592	.235	.090	.020	.325
-07	.438	.349	.438	.624	.235	.090	.020	.325
-08	.500	.380	.500	.655	.235	.090	.020	.325
-09	.562	.423	.562	.741	.256	.125	.032	.368
-10	.625	.454	.625	.772	.256	.125	.032	.368
-11	.688	.486	.688	.804	.256	.125	.032	.368
-12	.750	.517	.750	.835	.256	.125	.032	.368
-13	.812	.548	.812	.866	.256	.125	.032	.368
-14	.875	.580	.875	.898	.256	.125	.032	.368
-15	.938	.611	.938	.929	.256	.125	.032	.368
-16	1.000	.642	1.000	.960	.256	.125	.032	.368
-17	1.062	.681	1.062	1.001	.262	.125	.040	.370
-18	1.125	.712	1.125	1.032	.262	.125	.040	.370
-19	1.188	.744	1.188	1.064	.262	.125	.040	.370
-20	1.250	.775	1.250	1.095	.262	.125	.040	.370
-21	1.312	.806	1.312	1.126	.262	.125	.040	.370
-22	1.375	.838	1.375	1.158	.262	.125	.040	.370
-23	1.438	.869	1.438	1.189	.262	.125	.040	.370
-24	1.500	.900	1.500	1.220	.262	.125	.040	.370

NOTES:

1. MATERIALS:
 - BAND - 17-7PH, CORROSION RESISTANT STEEL PER AMS5528 OR AMS5529, ANNEALED
 - CUSHION - NITRILE BUTADIENE RUBBER, 65-75 DUROMETER, COLOR YELLOW, PER AMS3224
2. HEAT TREATMENT:
 - BAND - STRESS RELIEVE AND HEAT TREAT TO CONDITION TH1100 PER AMS2759/3 AFTER FORMING
 - CUSHION - NONE
3. FINISH:
 - BAND - REMOVE SCALE. PASSIVATE PER AMS2700 TYPE 2 OR 8
 - CUSHION - NONE
- /4/ DIAMETER "D" IS THE NOMINAL DIAMETER FOR WHICH A CLAMP SIZE IS INTENDED FOR USE. DIAMETER "D" SHALL BE VERIFIED BY THE "DIAMETER RETENTION" TEST OF THE PROCUREMENT SPECIFICATION. DIMENSION "E" SHALL BE MEASURED WITH THE CLAMP INSTALLED ON A MANDREL OF "D" DIAMETER ±.001 AND A .063±.001 GAP SPACER BETWEEN UPPER AND LOWER FOOT AS SHOWN.
- /5/ PROCUREMENT SPECIFICATION: AS85052 EXCEPT AS SPECIFIED ON THIS STANDARD. PRODUCT SUPPLIED TO THIS SPECIFICATION SHALL BE MANUFACTURED BY AN ACCREDITED MANUFACTURER LISTED IN THE PERFORMANCE REVIEW INSTITUTE (PRI) QUALIFIED PRODUCTS LIST (QPL) PRI-QPL-AS85052 FOR THIS STANDARD. SEE www.eauditnet.com FOR CURRENT QPL ON-LINE.
- /6/ WEDGE SHALL BE REQUIRED ON SIZE -06 AND LARGER. THE WEDGE SHALL BE MOLDED AS AN INTEGRAL PART OF THE CUSHION AND CONTOURED TO FIT "D" DIAMETER. WEDGE MUST TOUCH CUSHION ON LOWER FOOT WITH CLAMP INSTALLED ON A MANDREL WITHOUT SPACER.

	AEROSPACE STANDARD	AS85052/1 SHEET 2 OF 3	REV. A
	(R) CLAMP, LOOP, TUBE, 17-7PH, 275 °F, FUEL AND PETROLEUM BASED HYDRAULIC FLUID RESISTANT		