


SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. A			FEDERAL SUPPLY CLASS 5935
SAE AS90335	RATIONALE THE PRODUCTS COVERED BY THIS DOCUMENT ARE CURRENTLY COVERED BY AN ACTIVE MIL DOCUMENT (MIL-DTL-32385), WHICH MAKES THIS DOCUMENT A DUPLICATE, BUT AC WOULD NOT APPROVE CANCELLATION SO IT IS BEING STABILIZED. STABILIZED NOTICE THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY THE SAE AE-8C1 CONNECTORS COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.		
SAENORM.COM : Click to view the full PDF of as90335a			
SAE values your input. To provide feedback on this Technical Report, please visit http://www.sae.org/technical/standards/AS90335A		THIRD ANGLE PROJECTION 	
CUSTODIAN: A-20 STABILIZED BY AE-8C1		PROCUREMENT SPECIFICATION: NONE	
 An SAE International Group	AEROSPACE STANDARD CONNECTOR, RECEPTACLES, PLUGS, ADAPTOR, EL, EMBEDDED, PRINTED CIRCUIT BOARD LAMP LIGHTING PANELS		SAE AS90335 REV. A

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS90335D AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS90335D. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.


UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.


SAENORM.COM : Click to view the full PDF of as90335a


 An SAE International Group	AEROSPACE STANDARD	SAE AS90335 SHEET 1 OF 8	REV. A
	CONNECTOR, RECEPTACLES, PLUGS, ADAPTOR, EL, EMBEDDED, PRINTED CIRCUIT BOARD LAMP LIGHTING PANELS		




THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-P-7788.

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.











CENTER CONTACT POSITIVE
DASH NO. -7
FOR EMBEDDED
APPLICATION



CENTER CONTACT TAB BENDS MAY BE EXPOSED.

CENTER CONTACT POSITIVE
DASH NO. -8
FOR PRINTED CIRCUIT
BOARD APPLICATION



INCHES	MIL
.001	.03
.002	.05
.003	.08
.004	.10
.005	.13
.006	.15
.010	.25
.015	.30
.018	.46
.020	.51
.028	.71
.030	.76
.031	.79
.032	.81
.040	1.02
.043	1.09
.045	1.14
.050	1.27
.055	1.40
.060	1.52
.062	1.57
.070	1.70
.081	2.06
.083	2.11
.093	2.36
.100	2.54
.120	3.05
.124	3.15
.125	3.18
.130	3.30
.135	3.43
.140	3.56
.155	3.94
.170	4.32
.188	4.78
.190	4.83
.200	5.00
.210	5.33
.228	5.79
.240	6.10
.250	6.35
.257	6.40
.258	6.45
.280	7.11
.290	7.37
.295	7.49
.296	7.52
.297	7.54
.310	7.87
.312	7.92
.320	8.13
.326	8.28
.344	8.74
.355	9.02
.360	9.14
.375	9.52
.390	9.91
.400	10.16
.406	10.31
.430	10.92
.437	11.10
.441	11.20
.500	12.70
.520	13.21
.525	13.34
.531	13.49
.550	13.97
.563	14.30
.577	14.66
.590	14.99
.715	18.16
.718	18.24
.750	19.05
.805	20.45
.875	22.23
.906	23.01

NOTES:

1. MATERIAL: DASH NO. -1, -2, -3, -4, -5, -6, -9: BODY - BRASS PER ASTM B16, TEMPER H02; INSULATOR - POLYTETRAFLUOROETHYLENE PER ASTM D1710; CENTER CONTACT - BERYLLIUM COPPER PER ASTM B196, TEMPER TD04, HEAT TREAT PER MIL-H-7199.

DASH NO. -1, -2, -3, -4: SOLDER LUG - BRASS PER ASTM B36, TEMPER H02.

DASH NO. -5, -6: GROUND CONTACT - BRASS PER ASTM B16, TEMPER H02.

DASH NO. -7: CENTER PIN - BRASS PER ASTM B16, TEMPER H02; COLLAR - BERYLLIUM COPPER PER ASTM B196, TEMPER TD04, HEAT TREAT PER MIL-H-7199, BASE INSULATOR-METHACRYLATE PER L-P-380, CLEAR: ALTERNATE BASE INSULATORS - POLYVINYLIDENE FLUORIDE PER MIL-P-46122B, TYPE I, GRADE E, NATURAL; POLYCARBONATE PER ASTM D3935 PC110830720E01F02, CLEAR.

DASH NO. -8: CENTER PIN - BRASS PER ASTM B16, TEMPER H02; COLLAR - BERYLLIUM COPPER PER ASTM B196, TEMPER TD04, HEAT TREAT PER MIL-H-7199; BASE INSULATOR -POLYVINYLIDENE FLUORIDE PER 46122B, TYPE 1, GRADE E, NATURAL.