

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
C

AS92001™

FEDERAL SUPPLY CLASS
5310

RATIONALE

FIGURE REDRAWN, USAGE OF PART NOTE ADDED, FOLLOWING FIVE YEAR REVIEW.

NOTICE

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9200C, NOTICE 1. THIS SAE STANDARD MAY RETAIN THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL'S) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.





FIGURE 1 - NUT

SAE values your input. To provide feedback on this
Technical Report, please visit
<http://standards.sae.org/AS92001C>

THIRD ANGLE PROJECTION



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: NONE



AEROSPACE STANDARD

NUT, HEXAGON, DRILLED, BOSS
CONNECTION, ALUMINUM – UNS A92014

AS92001™
SHEET 1 OF 3

REV.
C

TABLE 1 – PART NUMBERS AND DIMENSIONS

PART NUMBER	NOM TUBE OD	D - NOMINAL THREAD	AF	E MIN	AB
MS9200-02	.125	.3125-24-UNJF-3B	.553- .564	.623	.312- .332
MS9200-03	.188	.3750-24UNJF-3B	.616- .627	.694	.375- .395
MS9200-04	.250	.4375-20UNJF-3B	.679- .690	.766	.438- .458
MS9200-05	.312	.5000-20UNJF-3B	.741- .752	.836	.500- .520
MS9200-06	.375	.5625-18UNJF-3B	.803- .814	.907	.562- .582
MS9200-07	.438	.6250-18UNJF-3B	.865- .877	.978	.625- .645
MS9200-08	.500	.7500-16UNJF-3B	.990-1.002	1.121	.750- .770
MS9200-09	.562	.8125-16UNJ-3B	1.052-1.064	1.191	.812- .832
MS9200-10	.625	.8750-14UNJF-3B	1.114-1.127	1.262	.875- .895
MS9200-11	.688	1.0000-12UNJF-3B	1.301-1.314	1.475	1.000-1.020
MS9200-12	.750	1.0625-12UNJ-3B	1.364-1.377	1.547	1.062-1.082
MS9200-14	.875	1.1875-12UNJ-3B	1.489-1.502	1.690	1.188-1.208
MS9200-16	1.000	1.3125-12UNJ-3B	1.614-1.627	1.833	1.312-1.332
MS9200-18	1.125	1.5000-12UNJ-3B	1.800-1.814	2.048	1.500-1.520
MS9200-20	1.250	1.6250-12UNJ-3B	1.926-1.940	2.189	1.625- 1.645
MS9200-24	1.500	1.8750-12UNJ-3B	2.176-2.190	2.474	1.875- 1.895
MS9200-28	1.750	2.2500-12UNJ-3B	2.549-2.564	2.899	2.250-2.270
MS9200-32	2.000	2.5000-12UNJ-3B	2.799-2.814	3.185	2.500- 2.520

TABLE 1 – PART NUMBERS AND DIMENSIONS (CONTINUED)

PART NUMBER	NOM TUBE OD	K	L MIN	P	T	J	APPROX MASS LB/100
MS9200-02	.125	.209-.229	.552	.110	.240	.042-.052	.43
MS9200-03	.188	.209-.229	.615	.110	.240	.042-.052	.49
MS9200-04	.250	.240-.260	.678	.125	.305	.042-.052	.66
MS9200-05	.312	.240-.260	.740	.125	.340	.050-.060	.75
MS9200-06	.375	.256-.276	.802	.133	.370	.050-.060	.88
MS9200-07	.438	.256-.276	.865	.133	.405	.050-.060	.99
MS9200-08	.500	.302-.322	.990	.157	.470	.057-.067	1.39
MS9200-09	.562	.302-.322	1.052	.157	.500	.057-.067	1.47
MS9200-10	.625	.349-.369	1.115	.180	.540	.057-.067	1.89
MS9200-11	.688	.396-.416	1.302	.204	.625	.065-.075	3.06
MS9200-12	.750	.396-.416	1.365	.204	.660	.065-.075	3.26
MS9200-14	.875	.396-.416	1.490	.204	.725	.065-.075	3.64
MS9200-16	1.000	.396-.416	1.615	.204	.790	.065-.075	4.07
MS9200-18	1.125	.396-.416	1.802	.204	.890	.065-.075	4.70
MS9200-20	1.250	.396-.416	1.928	.204	.960	.065-.075	5.15
MS9200-24	1.500	.396-.416	2.178	.204	1.095	.065-.075	6.06
MS9200-28	1.750	.396-.416	2.552	.204	1.295	.065-.075	7.47
MS9200-32	2.000	.396-.416	2.802	.204	1.425	.065-.075	8.47



AEROSPACE STANDARD

NUT, HEXAGON, DRILLED, BOSS
CONNECTION, ALUMINUM – UNS A92014

AS92001™
SHEET 2 OF 3

REV.
C