





SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

AS9209	REV. A		FEDERAL SUPPLY CLASS 5306					
		THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9209, NOTICE 1. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT. ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT. SAENORM.COM : Click to view the full PDF of as9209a <table border="1" style="border-collapse: collapse;"> <tr> <td style="padding: 2px;">THIRD ANGLE PROJECTION</td> </tr> <tr> <td style="text-align: center; padding: 10px;">  </td> </tr> </table>		THIRD ANGLE PROJECTION				
THIRD ANGLE PROJECTION								
								
PREPARED BY SAE COMMITTEE E-25, GENERAL STANDARDS FOR AEROSPACE PROPULSION SYSTEMS								
	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center; padding: 5px;">AEROSPACE STANDARD</td> </tr> <tr> <td style="padding: 5px;"> (R) BOLT, MACHINE - STEEL, DIFFUSED NICKEL-CADMIUM PLATED, DOUBLE HEXAGON EXTENDED WASHER HEAD, UNS K14675, 195 KSI MIN, .2500-28 UNJF-3A </td> </tr> </table>		AEROSPACE STANDARD	(R) BOLT, MACHINE - STEEL, DIFFUSED NICKEL-CADMIUM PLATED, DOUBLE HEXAGON EXTENDED WASHER HEAD, UNS K14675, 195 KSI MIN, .2500-28 UNJF-3A	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center; padding: 5px;"> AS9209 SHEET 1 OF 4 </td> </tr> </table>	AS9209 SHEET 1 OF 4	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center; padding: 5px;"> REV. A </td> </tr> </table>	REV. A
AEROSPACE STANDARD								
(R) BOLT, MACHINE - STEEL, DIFFUSED NICKEL-CADMIUM PLATED, DOUBLE HEXAGON EXTENDED WASHER HEAD, UNS K14675, 195 KSI MIN, .2500-28 UNJF-3A								
AS9209 SHEET 1 OF 4								
REV. A								

REV.
A

AS9209



REV.
A

AS9209

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	K	APPROX. MASS LB/100	PART NO.	L	K	APPROX. MASS LB/100
MS9209-04	.375	.079 - .099	1.14	MS9209-34	2.750	1.940 - 2.000	3.85
MS9209-05	.438	.079 - .099	1.21	MS9209-35	2.875	2.065 - 2.125	4.00
MS9209-06	.500	.079 - .099	1.29	MS9209-36	3.000	2.190 - 2.250	4.14
MS9209-07	.562	.079 - .099	1.36	MS9209-37	3.125	2.315 - 2.375	4.29
MS9209-08	.625	.079 - .099	1.44	MS9209-38	3.250	2.440 - 2.500	4.43
MS9209-09	.688	.079 - .099	1.51	MS9209-39	3.375	2.565 - 2.625	4.58
MS9209-10	.750	.079 - .099	1.58	MS9209-40	3.500	2.690 - 2.750	4.72
MS9209-11	.812	.079 - .099	1.65	MS9209-41	3.625	2.815 - 2.875	4.85
MS9209-12	.875	.125 - .145	1.72	MS9209-42	3.750	2.940 - 3.000	4.99
MS9209-13	.938	.128 - .188	1.79	MS9209-43	3.875	3.065 - 3.125	5.13
MS9209-14	1.000	.190 - .250	1.86	MS9209-44	4.000	3.190 - 3.250	5.27
MS9209-15	1.062	.252 - .312	1.93	MS9209-45	4.125	3.315 - 3.375	5.42
MS9209-16	1.125	.315 - .375	2.00	MS9209-46	4.250	3.440 - 3.500	5.56
MS9209-17	1.188	.378 - .438	2.08	MS9209-47	4.375	3.565 - 3.625	5.71
MS9209-18	1.250	.440 - .500	2.15	MS9209-48	4.500	3.690 - 3.750	5.85
MS9209-19	1.312	.502 - .562	2.22	MS9209-49	4.625	3.815 - 3.875	6.00
MS9209-20	1.375	.565 - .625	2.29	MS9209-50	4.750	3.940 - 4.000	6.14
MS9209-21	1.438	.628 - .688	2.36	MS9209-51	4.875	4.065 - 4.125	6.29
MS9209-22	1.500	.690 - .750	2.43	MS9209-52	5.000	4.190 - 4.250	6.43
MS9209-23	1.562	.752 - .812	2.50	MS9209-53	5.125	4.315 - 4.375	6.56
MS9209-24	1.625	.815 - .875	2.57	MS9209-54	5.250	4.440 - 4.500	6.70
MS9209-25	1.688	.878 - .938	2.64	MS9209-55	5.375	4.565 - 4.625	6.84
MS9209-26	1.750	.940 - 1.000	2.72	MS9209-56	5.500	4.690 - 4.750	6.99
MS9209-27	1.875	1.065 - 1.125	2.86	MS9209-57	5.625	4.815 - 4.875	7.13
MS9209-28	2.000	1.190 - 1.250	3.00	MS9209-58	5.750	4.940 - 5.000	7.28
MS9209-29	2.125	1.315 - 1.375	3.14	MS9209-59	5.875	5.065 - 5.125	7.42
MS9209-30	2.250	1.440 - 1.500	3.29	MS9209-60	6.000	5.190 - 5.250	7.57
MS9209-31	2.375	1.565 - 1.625	3.43				
MS9209-32	2.500	1.690 - 1.750	3.57				
MS9209-33	2.625	1.815 - 1.875	3.71				