


SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

REV. A	AS9217	FEDERAL SUPPLY CLASS 5306	
		THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9217(ASG), NOTICE 1. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT. ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.	
		THIRD ANGLE PROJECTION 	
PREPARED BY SAE COMMITTEE E-25, GENERAL STANDARDS FOR AEROSPACE PROPULSION SYSTEMS			
		AEROSPACE STANDARD (R) BOLT, MACHINE - STEEL, DIFFUSED NICKEL - CADMIUM PLATED, DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, UNS K14675, 195 KSI MIN, .190-32 UNJF-3A	AS9217 SHEET 1 OF 3
		REV. A	ISSUED 1998-11 REVISED 2002-12

REV.
A

AS9217




FIGURE 1 - SCREW

AEROSPACE STANDARDBOLT, MACHINE - STEEL, DIFFUSED NICKEL -
CADMIUM PLATED, DOUBLE HEXAGON
EXTENDED WASHER HEAD, DRILLED, UNS K14675,
195 KSI MIN, .190-32 UNJF-3A