


AS 931



HEX SIZE & HEX CHAMFER PER AS 930

DASH NO.	TUBE O.D.	THREAD T (REF.) MIL-S-8879	L ± .015	H HEX (REF.)	D DIA. (REF.)	F ± .010	Z (REF.)
-02	1/8	.3125-24 UNJF-3A	.955	.563	.093	.470	.200
-03	3/16	.3750-24 UNJF-3A	1.002	.625	.125	.470	.200
-04	1/4	.4375-20 UNJF-3A	1.088	.688	.187	.518	.235
-05	5/16	.5000-20 UNJF-3A	1.088	.750	.234	.518	.235
-06	3/8	.5625-18 UNJF-3A	1.119	.813	.297	.525	.250
-08	1/2	.7500-16 UNJF-3A	1.252	1.000	.422	.565	.250
-10	5/8	.8750-14 UNJF-3A	1.377	1.125	.500	.596	.312
-12	3/4	1.0625-12 UNJ-3A	1.543	1.375	.656	.667	.312
-16	1	1.3125-12 UNJ-3A	1.543	1.625	.875	.667	.375
-20	1-1/4	1.6250-12 UNJ-3A	1.543	1.875	1.093	.667	.375
-24	1-1/2	1.8750-12 UNJ-3A	1.543	2.125	1.344	.667	.375
-32	2	2.5000-12 UNJ-3A	1.605	2.750	1.813	.698	.437

REAFFIRMED
APRIL 1993

CUSTODIAN: SAE G-3/G-3B

PROCUREMENT: MIL-P-18280

SAE The Engineering Resource For Advancing Mobility
400 Commonwealth Drive
Warrendale, PA 15096

AEROSPACE STANDARD

ADAPTER - FLARELESS TUBE TO BOSS

AS 931

SHEET 1 OF 2

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.