

REV.
A

AS9401

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9401(ASG). THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.

WARNING

THIS DOCUMENT INCLUDES CADMIUM AS A PLATING MATERIAL. THE USE OF CADMIUM HAS BEEN RESTRICTED AND/OR BANNED FOR USE IN MANY COUNTRIES DUE TO ENVIRONMENTAL AND HEALTH CONCERNS. THE USER SHOULD CONSULT WITH LOCAL OFFICIALS ON THE ENVIRONMENTAL AND HEALTH REGULATIONS REGARDING ITS USE.




FIGURE 1 - BOLT

PREPARED BY SAE COMMITTEE E-25, GENERAL STANDARDS FOR AEROSPACE & PROPULSION SYSTEMS

SAE Aerospace
An SAE International Group

(R)

AEROSPACE STANDARD

BOLT, TEE HEAD - CADMIUM PLATED,
STEEL, UNS G87400, 125 KSI MIN,
CHAMFERED, .4375-20 UNJF-3A

AS9401
SHEET 1 OF 3

**REV.
A**

REV.
A

AS9401

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NUMBER	L	K	APPROX. MASS LB/100	PART NUMBER	L	K	APPROX. MASS LB/100
MS9401-06	.802 - .822	.155 - .175	6.23	MS9401-33	3.240 - 3.260	2.065 - 2.125	15.20
MS9401-07	.865 - .885	.155 - .175	6.56	MS9401-34	3.365 - 3.385	2.190 - 2.250	15.65
MS9401-08	.928 - .948	.155 - .175	6.78	MS9401-35	3.490 - 3.510	2.315 - 2.375	16.11
MS9401-09	.990 - 1.010	.155 - .175	7.01	MS9401-36	3.615 - 3.635	2.440 - 2.500	16.56
MS9401-10	1.052 - 1.072	.155 - .175	7.24	MS9401-37	3.740 - 3.760	2.565 - 2.625	17.02
MS9401-11	1.115 - 1.135	.155 - .175	7.46	MS9401-38	3.865 - 3.885	2.690 - 2.750	17.47
MS9401-12	1.178 - 1.198	.155 - .175	7.69	MS9401-39	3.990 - 4.010	2.815 - 2.875	17.93
MS9401-13	1.240 - 1.260	.155 - .175	7.92	MS9401-40	4.115 - 4.135	2.940 - 3.000	18.38
MS9401-14	1.302 - 1.322	.155 - .175	8.15	MS9401-41	4.240 - 4.260	3.065 - 3.125	18.83
MS9401-15	1.365 - 1.385	.190 - .250	8.37	MS9401-42	4.365 - 4.385	3.190 - 3.250	19.29
MS9401-16	1.428 - 1.448	.252 - .312	8.60	MS9401-43	4.490 - 4.510	3.315 - 3.375	19.74
MS9401-17	1.490 - 1.510	.315 - .375	8.83	MS9401-44	4.615 - 4.635	3.440 - 3.500	20.20
MS9401-18	1.552 - 1.572	.378 - .438	9.06	MS9401-45	4.740 - 4.760	3.565 - 3.625	20.65
MS9401-19	1.615 - 1.635	.440 - .500	9.28	MS9401-46	4.865 - 4.885	3.690 - 3.750	21.11
MS9401-20	1.678 - 1.698	.502 - .562	9.51	MS9401-47	4.990 - 5.010	3.815 - 3.875	21.56
MS9401-21	1.740 - 1.760	.565 - .625	9.74	MS9401-48	5.115 - 5.135	3.940 - 4.000	22.02
MS9401-22	1.865 - 1.885	.690 - .750	10.19	MS9401-49	5.240 - 5.260	4.065 - 4.125	22.47
MS9401-23	1.990 - 2.010	.815 - .875	10.65	MS9401-50	5.365 - 5.385	4.190 - 4.250	22.93
MS9401-24	2.115 - 2.135	.940 - 1.000	11.10	MS9401-51	5.490 - 5.510	4.315 - 4.375	23.38
MS9401-25	2.240 - 2.260	1.065 - 1.125	11.56	MS9401-52	5.615 - 5.635	4.440 - 4.500	23.84
MS9401-26	2.365 - 2.385	1.190 - 1.250	12.01	MS9401-53	5.740 - 5.760	4.565 - 4.625	24.29
MS9401-27	2.490 - 2.510	1.315 - 1.375	12.47	MS9401-54	5.865 - 5.885	4.690 - 4.750	24.75
MS9401-28	2.615 - 2.635	1.440 - 1.500	12.92	MS9401-55	5.990 - 6.010	4.815 - 4.875	25.20
MS9401-29	2.740 - 2.760	1.565 - 1.625	13.38				
MS9401-30	2.865 - 2.885	1.690 - 1.750	13.83				
MS9401-31	2.990 - 3.010	1.815 - 1.875	14.29				
MS9401-32	3.115 - 3.135	1.940 - 2.000	14.75				