

THIS DOCUMENT HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE 5-YEAR REVIEW POLICY.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.



REV.
A

SAE WEB ADDRESS: <http://www.sae.org>

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

ISSUED 1999-04	REVISED 2003-04	REAFFIRMED 2007-06
----------------	-----------------	--------------------

REV.
A

AS9503

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	K	APPROX. MASS LB/100	PART NO.	L	K	APPROX. MASS LB/100
MS9503-04	.615 - .635	.088 - .108	3.59	MS9503-33	3.115 - 3.135	2.065 - 2.125	11.37
MS9503-05	.678 - .698	.088 - .108	3.79	MS9503-34	3.240 - 3.260	2.190 - 2.250	11.77
MS9503-06	.740 - .760	.088 - .108	3.98	MS9503-35	3.365 - 3.385	2.315 - 2.375	12.16
MS9503-07	.802 - .822	.088 - .108	4.17	MS9503-36	3.490 - 3.510	2.440 - 2.500	12.55
MS9503-08	.865 - .885	.088 - .108	4.37	MS9503-37	3.615 - 3.635	2.565 - 2.625	12.94
MS9503-09	.928 - .948	.088 - .108	4.57	MS9503-38	3.740 - 3.760	2.690 - 2.750	13.33
MS9503-10	.990 - 1.010	.088 - .108	4.76	MS9503-39	3.865 - 3.885	2.815 - 2.875	13.72
MS9503-11	1.052 - 1.072	.088 - .108	4.95	MS9503-40	3.990 - 4.010	2.940 - 3.000	14.11
MS9503-12	1.115 - 1.135	.088 - .125	5.15	MS9503-41	4.115 - 4.135	3.065 - 3.125	14.50
MS9503-13	1.178 - 1.198	.128 - .188	5.34	MS9503-42	4.240 - 4.260	3.190 - 3.250	14.89
MS9503-14	1.240 - 1.260	.190 - .250	5.53	MS9503-43	4.365 - 4.385	3.315 - 3.375	15.28
MS9503-15	1.302 - 1.322	.252 - .312	5.73	MS9503-44	4.490 - 4.510	3.440 - 3.500	15.67
MS9503-16	1.365 - 1.385	.315 - .375	5.93	MS9503-45	4.615 - 4.635	3.565 - 3.625	16.06
MS9503-17	1.428 - 1.448	.378 - .438	6.12	MS9503-46	4.740 - 4.760	3.690 - 3.750	16.45
MS9503-18	1.490 - 1.510	.440 - .500	6.32	MS9503-47	4.865 - 4.885	3.815 - 3.875	16.84
MS9503-19	1.552 - 1.572	.502 - .562	6.51	MS9503-48	4.990 - 5.010	3.940 - 4.000	17.23
MS9503-20	1.615 - 1.635	.565 - .625	6.71	MS9503-49	5.115 - 5.135	4.065 - 4.125	17.62
MS9503-21	1.678 - 1.698	.628 - .688	6.90	MS9503-50	5.240 - 5.260	4.190 - 4.250	18.01
MS9503-22	1.740 - 1.760	.690 - .750	7.10	MS9503-51	5.365 - 5.385	4.315 - 4.375	18.40
MS9503-23	1.865 - 1.885	.815 - .875	7.49	MS9503-52	5.490 - 5.510	4.440 - 4.500	18.79
MS9503-24	1.990 - 2.010	.940 - 1.000	7.88	MS9503-53	5.615 - 5.635	4.565 - 4.625	19.17
MS9503-25	2.115 - 2.135	1.065 - 1.125	8.27	MS9503-54	5.740 - 5.760	4.690 - 4.750	19.56
MS9503-26	2.240 - 2.260	1.190 - 1.250	8.65	MS9503-55	5.865 - 5.885	4.815 - 4.875	19.95
MS9503-27	2.365 - 2.385	1.315 - 1.375	9.04	MS9503-56	5.990 - 6.010	4.940 - 5.000	20.34
MS9503-28	2.490 - 2.510	1.440 - 1.500	9.43	MS9503-57	1.802 - 1.822	.752 - .812	7.30
MS9503-29	2.615 - 2.635	1.565 - 1.625	9.82	MS9503-58	1.928 - 1.948	.878 - .938	7.69
MS9503-30	2.740 - 2.760	1.690 - 1.750	10.21				
MS9503-31	2.865 - 2.885	1.815 - 1.875	10.60				
MS9503-32	2.990 - 3.010	1.940 - 2.000	10.99				