

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NUMBER	L	K	APPROX MASS LB/100	PART NUMBER	L	K	APPROX MASS LB/100
MS9503-04	.615- .635	.088- .108	3.59	MS9503-32	2.990-3.010	1.940-2.000	10.99
MS9503-05	.678- .698	.088- .108	3.79	MS9503-33	3.115-3.135	2.065-2.125	11.37
MS9503-06	.740- .760	.088- .108	3.98	MS9503-34	3.240-3.260	2.190-2.250	11.77
MS9503-07	.802- .822	.088- .108	4.17	MS9503-35	3.365-3.885	2.315-2.375	12.16
MS9503-08	.865- .885	.088- .108	4.37	MS9503-36	3.490-3.510	2.440-2.500	12.55
MS9503-09	.928- .948	.088- .108	4.57	MS9503-37	3.615-3.635	2.565-2.625	12.94
MS9503-10	.990-1.010	.088- .108	4.76	MS9503-38	3.740-3.760	2.690-2.750	13.33
MS9503-11	1.052-1.072	.088- .108	4.95	MS9503-39	3.865-3.885	2.815-2.875	13.72
MS9503-12	1.115-1.135	.088- .125	5.15	MS9503-40	3.990-4.010	2.940-3.000	14.11
MS9503-13	1.178-1.198	.128- .188	5.34	MS9503-41	4.115-4.135	3.065-3.125	14.50
MS9503-14	1.240-1.260	.190- .250	5.53	MS9503-42	4.240-4.260	3.190-3.250	14.89
MS9503-15	1.302-1.322	.252- .312	5.73	MS9503-43	4.365-4.385	3.315-3.375	15.28
MS9503-16	1.365-1.385	.315- .375	5.93	MS9503-44	4.490-4.510	3.440-3.500	15.67
MS9503-17	1.428-1.448	.378- .438	6.12	MS9503-45	4.615-4.635	3.565-3.625	16.06
MS9503-18	1.490-1.510	.440- .500	6.32	MS9503-46	4.740-4.780	3.690-3.750	16.45
MS9503-19	1.552-1.572	.502- .562	6.51	MS9503-47	4.865-4.885	3.815-3.875	16.84
MS9503-20	1.615-1.635	.565- .625	6.71	MS9503-48	4.990-5.010	3.940-4.000	17.23
MS9503-21	1.678-1.698	.628- .688	6.90	MS9503-49	5.115-5.135	4.065-4.125	17.62
MS9503-22	1.740-1.760	.690- .750	7.10	MS9503-50	5.240-5.260	4.190-4.250	18.01
MS9503-57	1.802-1.822	.752- .812	7.30	MS9503-51	5.365-5.385	4.315-4.375	18.40
MS9503-23	1.865-1.885	.815- .875	7.49	MS9503-52	5.490-5.510	4.440-4.500	18.79
MS9503-58	1.928-1.948	.878- .938	7.69	MS9503-53	5.615-5.635	4.565-4.625	19.17
MS9503-24	1.990-2.010	.940-1.000	7.88	MS9503-54	5.740-5.760	4.690-4.750	19.56
MS9503-25	2.115-2.135	1.065-1.125	8.27	MS9503-55	5.865-5.885	4.815-4.875	19.95
MS9503-26	2.240-2.260	1.190-1.250	8.65	MS9503-56	5.990-6.010	4.940-5.000	20.34
MS9503-27	2.365-2.385	1.315-1.375	9.04				
MS9503-28	2.490-2.510	1.440-1.500	9.43				
MS9503-29	2.615-2.635	1.565-1.625	9.82				
MS9503-30	2.740-2.760	1.690-1.750	10.21				
MS9503-31	2.865-2.885	1.815-1.875	10.60				



AEROSPACE STANDARD

BOLT, MACHINE - HEXAGON HEAD, DRILLED,
1 HOLE, FULL SHANK, CRES, UNS S66286,
130 KSI MIN, .3750-24 UNJF-3A

AS9503™
SHEET 2 OF 3

REV.
C