


NOTICE

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.



THIRD ANGLE PROJECTION



PROCUREMENT SPECIFICATION: AS7477

REV.
D

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NUMBER	L	K	APPROX MASS LBF/100	PART NUMBER	L	K	APPROX MASS LBF/100
MS9557-04	.365 - .385	.079 - .099	1.14	MS9557-32	2.490 - 2.510	1.690 - 1.750	3.57
MS9557-05	.428 - .448	.079 - .099	1.21	MS9557-33	2.615 - 2.635	1.815 - 1.875	3.71
MS9557-06	.490 - .510	.079 - .099	1.29	MS9557-34	2.740 - 2.760	1.940 - 2.100	3.85
MS9557-07	.552 - .572	.079 - .099	1.37	MS9557-35	2.865 - 2.885	2.065 - 2.152	4.00
MS9557-08	.615 - .635	.079 - .099	1.44	MS9557-36	2.990 - 3.010	2.190 - 2.250	4.14
MS9557-09	.678 - .698	.079 - .099	1.51	MS9557-37	3.115 - 3.135	2.315 - 2.375	4.29
MS9557-10	.740 - .760	.079 - .099	1.58	MS9557-38	3.240 - 3.260	2.440 - 2.500	4.43
MS9557-11	.802 - .822	.079 - .099	1.65	MS9557-39	3.365 - 3.385	2.565 - 2.625	4.58
MS9557-12	.865 - .885	.079 - .125	1.72	MS9557-40	3.490 - 3.510	2.690 - 2.750	4.72
MS9557-13	.928 - .948	.128 - .188	1.79	MS9557-41	3.615 - 3.635	2.815 - 2.875	4.85
MS9557-14	.990 - 1.010	.190 - .250	1.86	MS9557-42	3.740 - 3.760	2.940 - 3.000	4.99
MS9557-15	1.052 - 1.072	.252 - .312	1.93	MS9557-43	3.865 - 3.885	3.065 - 3.125	5.13
MS9557-16	1.115 - 1.135	.315 - .375	2.00	MS9557-44	3.990 - 4.010	3.190 - 3.250	5.27
MS9557-17	1.178 - 1.198	.378 - .438	2.08	MS9557-45	4.115 - 4.135	3.315 - 3.375	5.42
MS9557-18	1.240 - 1.260	.440 - .500	2.15	MS9557-46	4.240 - 4.260	3.440 - 3.500	5.60
MS9557-19	1.302 - 1.322	.502 - .562	2.22	MS9557-47	4.365 - 4.385	3.565 - 3.625	5.71
MS9557-20	1.365 - 1.385	.565 - .625	2.29	MS9557-48	4.490 - 4.510	3.690 - 3.750	5.85
MS9557-21	1.428 - 1.448	.628 - .688	2.36	MS9557-49	4.615 - 4.635	3.815 - 3.875	6.00
MS9557-22	1.490 - 1.510	.690 - .750	2.43	MS9557-50	4.740 - 4.760	3.940 - 4.000	6.14
MS9557-23	1.552 - 1.572	.752 - .812	2.50	MS9557-51	4.865 - 4.885	4.065 - 4.125	6.29
MS9557-24	1.615 - 1.635	.815 - .875	2.57	MS9557-52	4.990 - 5.010	4.190 - 4.260	6.43
MS9557-25	1.678 - 1.698	.878 - .938	2.64	MS9557-53	5.115 - 5.135	4.315 - 4.375	6.58
MS9557-26	1.740 - 1.760	.940 - 1.000	2.72	MS9557-54	5.240 - 5.260	4.440 - 4.500	6.70
MS9557-61	1.802 - 1.822	1.002 - 1.062	2.79	MS9557-55	5.365 - 5.385	4.565 - 4.625	6.84
MS9557-27	1.865 - 1.885	1.065 - 1.125	2.86	MS9557-56	5.490 - 5.510	4.690 - 4.750	6.99
MS9557-62	1.928 - 1.948	1.128 - 1.188	2.93	MS9557-57	5.615 - 5.635	4.815 - 4.875	7.13
MS9557-28	1.990 - 2.010	1.190 - 1.250	3.00	MS9557-58	5.740 - 5.760	4.490 - 5.000	7.28
MS9557-29	2.115 - 2.135	1.315 - 1.375	3.14	MS9557-59	5.865 - 5.885	5.065 - 5.125	7.42
MS9557-30	2.240 - 2.260	1.440 - 1.500	3.29	MS9557-60	5.990 - 6.010	5.190 - 5.250	7.57
MS9557-31	2.365 - 2.385	1.565 - 1.625	3.43				

DASH NUMBERS 61 AND 62 ARE IN LENGTH ORDER