

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.




TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	K	APPROX. MASS LB/100	PART NO.	L	K	APPROX. MASS LB/100
MS9558-04	.490 - .510	.088 - .108	2.06	MS9558-34	2.990 - 3.010	2.065 - 2.125	6.58
MS9558-05	.552 - .572	.088 - .108	2.17	MS9558-35	3.115 - 3.135	2.190 - 2.250	6.80
MS9558-06	.615 - .635	.088 - .108	2.28	MS9558-36	3.240 - 3.260	2.315 - 2.375	7.03
MS9558-07	.678 - .698	.088 - .108	2.39	MS9558-37	3.365 - 3.385	2.440 - 2.500	7.27
MS9558-08	.740 - .760	.088 - .108	2.51	MS9558-38	3.490 - 3.510	2.565 - 2.625	7.50
MS9558-09	.802 - .822	.088 - .108	2.62	MS9558-39	3.615 - 3.635	2.690 - 2.750	7.73
MS9558-10	.865 - .885	.088 - .108	2.73	MS9558-40	3.740 - 3.760	2.815 - 2.875	7.95
MS9558-11	.928 - .948	.088 - .108	2.85	MS9558-41	3.865 - 3.885	2.940 - 3.000	8.17
MS9558-12	.990 - 1.010	.088 - .125	2.96	MS9558-42	3.990 - 4.010	3.065 - 3.125	8.40
MS9558-13	1.052 - 1.072	.128 - .188	3.07	MS9558-43	4.115 - 4.135	3.190 - 3.250	8.63
MS9558-14	1.115 - 1.135	.190 - .250	3.19	MS9558-44	4.240 - 4.260	3.315 - 3.375	8.86
MS9558-15	1.178 - 1.198	.252 - .312	3.30	MS9558-45	4.365 - 4.385	3.440 - 3.500	9.08
MS9558-16	1.240 - 1.260	.315 - .375	3.41	MS9558-46	4.490 - 4.510	3.565 - 3.625	9.30
MS9558-17	1.302 - 1.322	.378 - .438	3.52	MS9558-47	4.615 - 4.635	3.690 - 3.750	9.52
MS9558-18	1.365 - 1.385	.440 - .500	3.64	MS9558-48	4.740 - 4.760	3.815 - 3.875	9.74
MS9558-19	1.428 - 1.448	.502 - .562	3.75	MS9558-49	4.865 - 4.885	3.940 - 4.000	9.95
MS9558-20	1.490 - 1.510	.565 - .625	3.87	MS9558-50	4.990 - 5.010	4.065 - 4.125	10.17
MS9558-21	1.552 - 1.572	.628 - .688	3.98	MS9558-51	5.115 - 5.135	4.190 - 4.250	10.40
MS9558-22	1.615 - 1.635	.690 - .750	4.10	MS9558-52	5.240 - 5.260	4.315 - 4.375	10.63
MS9558-23	1.678 - 1.698	.752 - .812	4.22	MS9558-53	5.365 - 5.385	4.440 - 4.500	10.86
MS9558-24	1.740 - 1.760	.815 - .875	4.33	MS9558-54	5.490 - 5.510	4.565 - 4.625	11.10
MS9558-25	1.865 - 1.885	.940 - 1.000	4.55	MS9558-55	5.615 - 5.635	4.690 - 4.750	11.33
MS9558-26	1.990 - 2.010	1.065 - 1.125	4.77	MS9558-56	5.740 - 5.760	4.815 - 4.875	11.56
MS9558-27	2.115 - 2.135	1.190 - 1.250	5.00	MS9558-57	5.865 - 5.885	4.940 - 5.000	11.78
MS9558-28	2.240 - 2.260	1.315 - 1.375	5.23	MS9558-58	5.990 - 6.010	5.065 - 5.125	12.00
MS9558-29	2.365 - 2.385	1.440 - 1.500	5.45	MS9558-59	1.802 - 1.822	.878 - .938	4.44
MS9558-30	2.490 - 2.510	1.565 - 1.625	5.67	MS9558-60	1.928 - 1.948	1.002 - 1.062	4.66
MS9558-31	2.615 - 2.635	1.690 - 1.750	5.90				
MS9558-32	2.740 - 2.760	1.815 - 1.875	6.13				
MS9558-33	2.865 - 2.885	1.940 - 2.000	6.36				