

REV. B				FEDERAL SUPPLY CLASS 5306
AS9568	NOTICE THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9568, NOTICE 1. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT. ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.			
SAENORM.COM : Click to view the full PDF of as9568b				
CUSTODIAN: SAE E-25				
 SAE Aerospace An SAE International Group	AEROSPACE STANDARD		AS9568 SHEET 1 OF 3	REV. B
	(R) BOLT, MACHINE, DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, 130 KSI MIN, .3750-24 UNJF-3A			
Copyright © 2003 SAE International All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE. TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada) Tel: 724-776-4970 (outside USA) Email: custsvc@sae.org SAE WEB ADDRESS: http://www.sae.org				




TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NUMBER	L	K	APPROX. MASS LB/100	PART NUMBER	L	K	APPROX MASS LB/100
MS9568-03	.562	.088-.108	3.26	MS9568-21	1.688	.628- .688	6.27
MS9568-04	.625	.088-.108	3.42	MS9568-22	1.750	.690- .750	6.44
MS9568-05	.688	.088-.108	3.58	MS9568-57	1.812	.752- .812	6.61
MS9568-06	.750	.088-.108	3.74	MS9568-23	1.875	.815- .875	6.77
MS9568-07	.812	.088-.08	3.90	MS9568-58	1.938	.878- .938	6.94
MS9568-08	.875	.088-.108	4.07	MS9568-24	2.000	.940-1.000	7.11
MS9568-09	.938	.088-.108	4.24	MS9568-25	2.125	1.065-1.125	7.44
MS9568-10	1.000	.088-.108	4.41	MS9568-26	2.250	1.190-1.250	7.78
MS9568-11	1.062	.088-.108	4.58	MS9568-27	2.375	1.315-1.375	8.11
MS9568-12	1.125	.088-.125	4.75	MS9568-28	2.500	1.440-1.500	8.44
MS9568-13	1.188	.125-.188	4.91	MS9568-29	2.625	1.565-1.625	8.78
MS9568-14	1.250	.190-.250	5.06	MS9568-30	2.750	1.690-1.750	9.12
MS9568-15	1.312	.252-.312	5.25	MS9568-31	2.875	1.815-1.875	9.46
MS9568-16	1.375	.315-.375	5.43	MS9568-32	3.000	1.940-2.000	9.80
MS9568-17	1.438	.378-.438	5.60	MS9568-33	3.125	2.065-2.125	10.13
MS9568-18	1.500	.440-.500	5.76				
MS9568-19	1.562	.502-.562	5.93				
MS9568-20	1.625	.585-.625	6.10				