


REV. C				FEDERAL SUPPLY CLASS 5306
AS9568	THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9568, NOTICE 1, AMENDMENT 1. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT. ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.			
SAENORM.COM : Click to view the full PDF of as9568c				
 SAE 100 Leading Our World In Motion		THIRD ANGLE PROJECTION 		
CUSTODIAN: SAE E-25				
 SAE Aerospace An SAE International Group	AEROSPACE STANDARD (R) BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, CRES UNS S66286, 130 KSI MIN .3750-24 UNJF-3A	AS9568 SHEET 1 OF 4	REV. C	

ISSUED 1998-08 REVISED 2005-07




TABLE 1 - PART NUMBERS AND DIMENSIONS.

PART NUMBER	L	K	APPROX. MASS LB/100	PART NUMBER	L	K	APPROX. MASS LB/100
MS9568-03	.552 - .572	.088 - .108	3.26	MS9568-29	2.615 - 2.635	1.565 - 1.625	8.78
MS9568-04	.615 - .635	.088 - .108	3.42	MS9568-30	2.740 - 2.760	1.690 - 1.750	9.12
MS9568-05	.678 - .698	.088 - .108	3.58	MS9568-31	2.865 - 2.885	1.815 - 1.875	9.48
MS9568-06	.740 - .760	.088 - .108	3.74	MS9568-32	2.990 - 3.010	1.940 - 2.000	9.80
MS9568-07	.802 - .822	.088 - .108	3.90	MS9568-33	3.115 - 3.135	2.065 - 2.125	10.13
MS9568-08	.865 - .885	.088 - .108	4.07	MS9568-34	3.240 - 3.260	2.190 - 2.250	10.47
MS9568-09	.928 - .948	.088 - .108	4.24	MS9568-35	3.365 - 3.385	2.315 - 2.375	10.80
MS9568-10	.990 - 1.010	.088 - .108	4.41	MS9568-36	3.490 - 3.510	2.440 - 2.500	11.14
MS9568-11	1.052 - 1.072	.088 - .108	4.58	MS9568-37	3.615 - 3.635	2.565 - 2.625	11.47
MS9568-12	1.115 - 1.135	.088 - .125	4.75	MS9568-38	3.740 - 3.760	2.690 - 2.750	11.80
MS9568-13	1.178 - 1.198	.128 - .188	4.91	MS9568-39	3.865 - 3.885	2.815 - 2.875	12.14
MS9568-14	1.240 - 1.260	.190 - .250	5.08	MS9568-40	3.990 - 4.010	2.940 - 3.000	12.47
MS9568-15	1.302 - 1.322	.252 - .312	5.25	MS9568-41	4.115 - 4.135	3.065 - 3.125	12.80
MS9568-16	1.365 - 1.385	.315 - .375	5.43	MS9568-42	4.240 - 4.260	3.190 - 3.250	13.13
MS9568-17	1.428 - 1.448	.378 - .438	5.60	MS9568-43	4.365 - 4.385	3.315 - 3.375	13.46
MS9568-18	1.490 - 1.510	.440 - .500	5.76	MS9568-44	4.490 - 4.510	3.440 - 3.500	13.89
MS9568-19	1.552 - 1.572	.502 - .562	5.93	MS9568-45	4.615 - 4.635	3.565 - 3.625	14.23
MS9568-20	1.615 - 1.635	.565 - .625	6.10	MS9568-46	4.740 - 4.760	3.690 - 3.750	14.56
MS9568-21	1.678 - 1.698	.628 - .688	6.27	MS9568-47	4.865 - 4.885	3.815 - 3.875	14.89
MS9568-22	1.740 - 1.760	.690 - .750	6.44	MS9568-48	4.990 - 5.010	3.940 - 4.000	15.23
MS9568-57	1.802 - 1.822	.752 - .812	6.61	MS9568-49	5.115 - 5.135	4.065 - 4.125	15.57
MS9568-23	1.865 - 1.885	.815 - .875	6.77	MS9568-50	5.240 - 5.260	4.190 - 4.250	15.90
MS9568-58	1.928 - 1.948	.878 - .938	6.94	MS9568-51	5.365 - 5.385	4.315 - 4.375	16.23
MS9568-24	1.990 - 2.010	.940 - 1.000	7.11	MS9568-52	5.490 - 5.510	4.440 - 4.500	16.56
MS9568-25	2.115 - 2.135	1.065 - 1.125	7.44	MS9568-53	5.615 - 5.635	4.565 - 4.625	16.89
MS9568-26	2.240 - 2.260	1.190 - 1.250	7.78	MS9568-54	5.740 - 5.760	4.690 - 4.750	17.23
MS9568-27	2.365 - 2.385	1.315 - 1.375	8.11	MS9568-55	5.865 - 5.885	4.815 - 4.875	17.57
MS9568-28	2.490 - 2.510	1.440 - 1.500	8.44	MS9568-56	5.990 - 6.010	4.940 - 5.000	17.91