


ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.



THIRD ANGLE PROJECTION



REV.
A

TABLE 1 - PART NUMBERS AND DIMENSIONS.

PART NUMBER	L	K	APPROX. MASS LB/100	PART NUMBER	L	K	APPROX. MASS LB/100
MS9698-04	.490 - .510	.088 - .108	2.17	MS9698-32	2.615 - 2.635	1.690 - 1.750	6.19
MS9698-05	.552 - .572	.088 - .108	2.29	MS9698-33	2.740 - 2.760	1.815 - 1.875	6.42
MS9698-06	.615 - .635	.088 - .108	2.41	MS9698-34	2.865 - 2.885	1.940 - 2.000	6.66
MS9698-07	.678 - .698	.088 - .108	2.52	MS9698-35	2.990 - 3.010	2.065 - 2.125	6.90
MS9698-08	.740 - .760	.088 - .108	2.64	MS9698-36	3.115 - 3.135	2.190 - 2.250	7.13
MS9698-09	.802 - .822	.088 - .108	2.76	MS9698-37	3.240 - 3.260	2.315 - 2.375	7.36
MS9698-10	.865 - .885	.088 - .108	2.88	MS9698-38	3.365 - 3.385	2.440 - 2.500	7.60
MS9698-11	.928 - .948	.088 - .108	3.00	MS9698-39	3.490 - 3.510	2.565 - 2.625	7.84
MS9698-12	.990 - 1.010	.088 - .125	3.11	MS9698-40	3.615 - 3.635	2.690 - 2.750	8.07
MS9698-13	1.052 - 1.072	.128 - .188	3.23	MS9698-41	3.740 - 3.760	2.815 - 2.875	8.31
MS9698-14	1.115 - 1.135	.190 - .250	3.35	MS9698-42	3.865 - 3.885	2.940 - 3.000	8.54
MS9698-15	1.178 - 1.198	.252 - .312	3.47	MS9698-43	3.990 - 4.010	3.065 - 3.125	8.78
MS9698-16	1.240 - 1.260	.315 - .375	3.59	MS9698-44	4.115 - 4.135	3.190 - 3.250	9.02
MS9698-17	1.302 - 1.322	.378 - .438	3.70	MS9698-45	4.240 - 4.260	3.315 - 3.375	9.25
MS9698-18	1.365 - 1.385	.440 - .500	3.82	MS9698-46	4.365 - 4.385	3.440 - 3.500	9.49
MS9698-19	1.428 - 1.448	.502 - .562	3.94	MS9698-47	4.490 - 4.510	3.565 - 3.625	9.72
MS9698-20	1.490 - 1.510	.565 - .625	4.06	MS9698-48	4.615 - 4.635	3.690 - 3.750	9.96
MS9698-21	1.552 - 1.572	.628 - .688	4.18	MS9698-49	4.740 - 4.760	3.815 - 3.875	10.20
MS9698-22	1.615 - 1.635	.690 - .750	4.29	MS9698-50	4.865 - 4.885	3.940 - 4.000	10.43
MS9698-23	1.678 - 1.698	.752 - .812	4.41	MS9698-51	4.990 - 5.010	4.065 - 4.125	10.67
MS9698-24	1.740 - 1.760	.815 - .875	4.53	MS9698-52	5.115 - 5.135	4.190 - 4.250	10.91
MS9698-25	1.802 - 1.822	.877 - .938	4.65	MS9698-53	5.240 - 5.260	4.315 - 4.375	11.14
MS9698-26	1.865 - 1.885	.940 - 1.000	4.77	MS9698-54	5.365 - 5.385	4.440 - 4.500	11.38
MS9698-27	1.990 - 2.010	1.065 - 1.125	5.00	MS9698-55	5.490 - 5.510	4.565 - 4.625	11.61
MS9698-28	2.115 - 2.135	1.190 - 1.250	5.24	MS9698-56	5.615 - 5.635	4.690 - 4.750	11.85
MS9698-29	2.240 - 2.260	1.315 - 1.375	5.48	MS9698-57	5.740 - 5.760	4.815 - 4.875	12.09
MS9698-30	2.365 - 2.385	1.440 - 1.500	5.71	MS9698-58	5.865 - 5.885	4.940 - 5.000	12.32
MS9698-31	2.490 - 2.510	1.565 - 1.625	5.95	MS9698-59	5.990 - 6.010	5.065 - 5.125	12.56