

AS9844

FEDERAL SUPPLY CLASS
5315

NOTICE


THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS9844, NOTICE 1 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS9844, NOTICE 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

SAENORM.COM : Click to view the full PDF of as9844

THIRD ANGLE PROJECTION



ISSUED 1999-08

PREPARED BY SAE COMMITTEE E-25

PROCUREMENT SPECIFICATION: NONE

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space®
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

PIN, STRAIGHT, HEADED,
.1874 DIAMETER, AMS 5616

AS9844
SHEET 1 OF 3

AS9844	
--------	--




FIGURE 1

TABLE 1

PART NO.	A	L	APPROX WEIGHT LB/100	PART NO.	A	L	APPROX WEIGHT LB/100	PART NO.	A	L	APPROX WEIGHT LB/100
MS9844-04	.253	.325	.310	MS9844-21	1.315	1.390	1.140	MS9844-36	2.253	2.328	1.880
MS9844-05	.315	.390	.360	MS9844-22	1.378	1.453	1.200	MS9844-37	2.315	2.390	1.930
				MS9844-23	1.440	1.515	1.240	MS9844-38	2.378	2.453	1.980
				MS9844-24	1.503	1.578	1.290	MS9844-39	2.440	2.515	2.030
				MS9844-25	1.565	1.640	1.340	MS9844-40	2.503	2.578	2.080
MS9844-06	.378	.453	.410	MS9844-26	1.628	1.703	1.390	MS9844-41	2.565	2.650	2.140
MS9844-07	.440	.515	.460	MS9844-27	1.690	1.765	1.440	MS9844-42	2.628	2.703	2.180
MS9844-08	.503	.578	.510	MS9844-28	1.753	1.828	1.490	MS9844-43	2.690	2.765	2.220
MS9844-09	.565	.640	.550	MS9844-29	1.815	1.890	1.540	MS9844-44	2.753	2.828	2.280
MS9844-10	.628	.703	.600	MS9844-30	1.878	1.953	1.590	MS9844-45	2.815	2.890	2.320
MS9844-11	.690	.765	.650	MS9844-31	1.940	2.015	1.640	MS9844-46	2.878	2.953	2.370
MS9844-12	.753	.828	.700	MS9844-32	2.003	2.078	1.690				
MS9844-13	.815	.890	.750	MS9844-33	2.065	2.140	1.730				
MS9844-14	.878	.953	.800	MS9844-34	2.128	2.203	1.780				
MS9844-15	.940	1.015	.850	MS9844-35	2.190	2.265	1.830				
MS9844-16	1.003	1.078	.900								
MS9844-17	1.005	1.140	.950								
MS9844-18	1.128	1.203	1.000								
MS9844-19	1.190	1.265	1.050								
MS9844-20	1.253	1.328	1.100								

NOTES:

1. MATERIAL: AMS 5616.
2. HARDNESS: ROCKWELL C45-50.
3. FLUORESCENT PENETRANT INSPECTION PER AMS 2645.
4. HEAD DIA. TO BE CONCENTRIC WITH SHANK DIA. WITHIN .003 FIR.