

A Product of the
Cooperative Engineering Program

SAE J1253 MAR86

**Low Temperature
Cranking Load
Requirements of an
Engine**

SAE Recommended Practice
Revised March 1986

SAENORM.COM :: Click to view the PDF of J1253-198603

**S. A. E.
LIBRARY**

Submitted for Recognition as
an American National Standard



*This standard is indexed
in the Standards Search Database*

SAENORM.COM : Click to view the full PDF of J1253_198603

**No part of this publication may be reproduced in any form,
in an electronic retrieval system or otherwise, without the
prior written permission of the publisher.**

Copyright 1986 Society of Automotive Engineers, Inc.

RATIONALE:

Not applicable.

RELATIONSHIP OF SAE STANDARD TO ISO STANDARD:

Not applicable.

REFERENCE SECTION:

SAE J300, Engine Oil Viscosity Classification for Method of Measurement and Definition

SAE J544, Electric Starting Motor Test Procedure

APPLICATION:

The electrical cranking system components, which include the battery, cables, and cranking motor, must be carefully selected to provide the necessary speed to start an engine under the most severe climatic conditions for which the system is intended. Engine cranking loads increase with cold temperatures, therefore, the initial selection of these components needs to consider low temperature engine torque requirements. To insure an adequate electrical cranking system is obtained, it is important that proper test procedures are used for obtaining the cranking load requirements of the engine.

COMMITTEE COMPOSITION:

DEVELOPED BY THE CRANKING MOTOR SUBCOMMITTEE:

S. B. Parker, GMC, Anderson, IN - Chairman
J. J. Augustine, Ford Motor Co., Dearborn, MI
A. J. Barber, Lucas Industries Inc., Troy, MI
D. G. Baugher, Chrysler Corporation, Detroit, MI
P. J. DePaulis, Amer. Motors Corp., Detroit, MI
C. M. Hayes, Allied Automotive, Bay City, MI
J. L. Kruse, Cummins Eng. Co., Inc., Columbus, IN
J. R. Tallis, Jr., Facet Enterprises, Inc., Elmira, NY

SPONSORED BY THE SAE ELECTRICAL AND ELECTRONIC SYSTEMS TECHNICAL COMMITTEE:

N. S. Hatch, GMC, Warren, OH - Chairman
J. B. King, Allegheny Int'l., Pittsburgh, PA - Vice Chairman
J. G. Rivard, Ford Motor Co., Dearborn, MI - Sponsor
F. Bauer, Dearborn, MI
A. J. Burgess, Lucas Industries Inc., Troy, MI
M. L. Crawford, Department of Commerce, Boulder, CO
W. L. Doelp, Jr., Ford Motor Co., Dearborn, MI
J. D. Fobian, American Automobile Association, Falls Church, VA
P. C. Franklin, Sheller-Globe Corp., Cleveland, OH
J. T. Hardin, Septor Electronics, El Paso, TX
M. E. Hartz, United Technologies Corp., E. Hartford, CT
R. E. Heller, Tenneco Inc., Hinsdale, IL

COMMITTEE COMPOSITION (Continued):

P. Hubbard, Ford Motor Co., Allen Park, MI
R. W. Johnson, Chrysler Corp., Detroit, MI
L. L. Kent, Bendix Corporation, Newport News, VA
R. W. MacKay, Toledo, OH
P. M. Marks, American Motors Corp., Detroit, MI
J. W. Mueller, Chrysler Corporation, Detroit, MI
S. B. Parker, GMC, Anderson, IN
J. R. Pierson, Johnson Controls, Inc., Milwaukee, WI
R. S. Podiak, Champion Spark Plug Co., Toledo, OH
T. Shewchuck, Ford Motor Co., Dearborn, MI
F. L. Zeisler, Lawrence Inst. of Tech., Southfield, MI
J. F. Ziomek, TRW, Inc., Farmington Hills, MI

SAENORM.COM : Click to view the full PDF of J1253_198603

**LOW TEMPERATURE CRANKING LOAD REQUIREMENTS
OF AN ENGINE**

1. **PURPOSE:** The electrical cranking system components, which include the battery, cables, and cranking motor, must be carefully selected to provide the necessary speed to start an engine under the most severe climatic conditions for which the system is intended. Engine cranking loads increase with cold temperatures, therefore, the initial selection of these components needs to consider low temperature engine torque requirements. To insure an adequate electrical cranking system is obtained, it is important that proper test procedures are used for obtaining the cranking load requirements of the engine.
2. **PROCEDURE:** The following test procedure is recommended for obtaining low temperature cranking torque requirements:
 - 2.1 **Engine Preparation:**
 - 2.1.1 The engine to be tested should be equipped with all accessories that provide parasitic loads, such as power steering pump, automatic transmission, etc.
 - 2.1.2 The engine, if new, should be run in to stabilize friction loads--equivalent to 1500 miles or 18 h at 2400 engine rpm.
 - 2.1.3 The engine is winterized with anti-freeze solution for the temperature at which the test will be run.
 - 2.1.4 The engine oil selected for the low temperature test should be representative of the high limit viscosity for the SAE grade recommended by the engine manufacturer for the operating temperature range (refer to SAE J300, Engine Oil Viscosity Classification for Method of Measurement and Definition). Sufficient oil of the same viscosity should be obtained for the complete test program so variations in test results can be minimized.

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

- 2.1.5 Fuel dilution of the engine oil will reduce its viscosity, therefore, to avoid this possibility, the cranking test is run without fuel in the carburetor, or with fuel system cut off.
- 2.1.6 To prepare the engine for test, the engine is warmed up and oil drained hot. This procedure should be repeated two times to assure complete change of oil when oil grade change is made. The oil filter is changed for the final fill. When the same grade of oil is used for other test temperatures and/or additional test days, the engine warm up procedure is repeated and only one drain is required.
- 2.1.7 Install a thermocouple in the center of the greatest mass of oil so soak temperatures can be monitored.
- 2.1.8 Equip engine with necessary instrumentation to provide cranking speed, battery voltage, cranking motor voltage, and current data. (The cranking speed can be determined from oscillographic current or voltage traces by calculation of the time span between the current or voltage peaks caused by the cylinder compression loads. The mean cranking speed is obtained over two consecutive revolutions. The mean torque is obtained by measuring the mean cranking current over the same period and calculated as described in paragraph 2.2.)
- 2.1.9 Prior to starting the cold soak period, warm up the engine for approximately 5-10 min to circulate oil, run carburetor bowl dry and disable ignition or cut off fuel system for diesels and adjust throttle plate to the idle position.
- 2.1.10 The engine with the calibrated motor is soaked at the test temperature θ for a period of 16-24 h, which can be monitored by the oil thermocouple.
- 2.2 Cranking Motor Preparation: The cranking motor is used to measure the engine cranking torque. To minimize performance variances, a new cranking motor should be "run in" until the motor performance becomes stabilized prior to calibration which is determining the speed, torque, and current under load using a standard SAE terminal voltage curve (Ref. Table 1 of SAE J544, Electric Starting Motor Test Procedure) unless otherwise specified.

After completion of the cranking load tests, a re-calibration curve should be run to verify initial performance.

Note: Since torque is proportional to cranking motor current, determination of engine torque can be calculated by obtaining the cranking motor running torque corresponding to the cranking motor current measured at the test temperature from the performance characteristics of the calibrated cranking motor and multiplying this value by the proper flywheel ring gear to cranking motor pinion gear ratio.