



SURFACE VEHICLE STANDARD

J1272

FEB2015

Issued 1979-10
Reaffirmed 2015-02

Superseding J1272 MAY2008

Felling Head Terminology and Nomenclature

RATIONALE

J1272 has been reaffirmed to comply with the SAE five-year review policy.

1. Scope—This SAE Standard is intended to describe the basic types of felling heads, including those with bunching capabilities, that are attachments to a self-propelled machine. Only the major components that are necessary to describe the functions of the felling head, and to apply the principles of the standard are included. Illustrations used are not intended to include all existing felling heads or to describe any particular manufacturer's variation.

1.1 Purpose—The purpose of this document is to set forth accepted definitions for functions of tree felling heads and to classify and establish nomenclature for major components and parts peculiar to these machines.

2. Reference

2.1 Applicable Publication—The following publication forms a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

2.1.1 SAE PUBLICATION—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J1209—Identification Terminology of Mobile Forestry Machines

3. Definitions

3.1 Accumulating—The process of collecting and holding multiple trees or stems for subsequent bunching.

3.2 Bunching—See SAE J1209.

3.3 Carriage—A movable frame driven by suitable means to advance the saw disc through the tree and retract the saw after the tree is cut.

3.4 Drive to Tree—A tree felling method in which the entire machine is maneuvered to position the felling head at the tree to be felled.

3.5 Felling—See SAE J1209.

3.6 Felling Head—A mechanism carried by a self-propelled machine for felling trees. The felling head may contain provisions for accumulating and/or bunching

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2015 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J1272_201502

4. Classifications

4.1 Shear Felling Heads

- 4.1.1 PIVOTED SINGLE BLADE—Felling is by single shear blade that travels in an arc about an axis perpendicular to the plane of cutting and works against an anvil for cutting (Figure 1).




FIGURE 1—PIVOTED SINGLE BLADE

4.1.2 PIVOTED DOUBLE BLADES—Felling is by two shear blades that travel in arcs of planar motion about one or more axes perpendicular to the plane of cutting. The blades work toward each other (Figure 2).




FIGURE 2—PIVOTED DOUBLE BLADES

4.2 Cutting Felling Heads

- 4.2.1 SAW CHAIN—Felling is by use of a saw chain guide bar. A shear blade may be incorporated to cut small diameter trees or for making the final cut (Figure 3).




FIGURE 3—SAW CHAIN

4.2.2 CIRCULAR DISK—Felling is by one or more horizontal rotating disks with peripheral cutters.

4.2.2.1 *Continuous Disk*—The disk is rotated constantly at high speed with lower torque. The inertia of the high-speed disk stores energy sufficient to cut the tree (Figures 4A and 4B).




FIGURE 4A—CIRCULAR SAW CONTINUOUS SWING TO TREE




FIGURE 4B—CIRCULAR SAW CONTINUOUS
DRIVE TO TREE