



SURFACE VEHICLE RECOMMENDED PRACTICE

J1638

APR2015

Issued 1993-05
Stabilized 2015-04

Superseding J1638 NOV2004

Compression Set of Hoses or Solid Discs

RATIONALE

This document has been determined to contain basic and stable technology which is not dynamic in nature.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE Non-Hydraulic Hose Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of J1638 - 201504

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2015 SAE International


All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

SAE values your input. To provide feedback on
this Technical Report, please visit
http://www.sae.org/technical/standards/J1638_201504


1. **Scope**—This SAE Recommended Practice is used for establishing the compression set that could be expected to occur with a thermoset elastomeric hose under securing clamps. It seeks to reproduce the type of indentation caused by the clamps in the wall of a hose. An excessive compression set measured by this method may indicate a hose that could eventually allow leakage of fluid or gas past the clamps in service.
2. **References**
 - 2.1 **Applicable Publications**—The following publications form a part of this specification to the extent specified herein.
 - 2.1.1 ASTM PUBLICATIONS—Available from ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.
 - ASTM D 3767—Practice for Rubber—Measurement of Dimensions
 - ASTM E 145—Specification for Gravity-Convection and Forced-Ventilation Ovens
3. **Apparatus Required**
 - 3.1 **Compression Fixture**—Refer to Figures 1 through 4.
 - 3.2 **Dial Micrometer**—For use in measuring thickness according to ASTM D 3767, Method A1. The measuring foot shall be flat with a diameter of $2.5 \text{ mm} \pm 0.1 \text{ mm}$ and a load of 45 g.
 - 3.3 **Feeler Gages or Gage Blocks**—For setting the specified compression under the indicators.
 - 3.4 **Air-Circulating Oven**—Conforming to ASTM E 145, Type IIA.



Compression Set Fixture Assembly

1) All Items Stainless Steel

FIGURE 1—SECTIONAL VIEW OF COMPRESSION SET FIXTURES



Loading Screw

FIGURE 2—LOADING SCREW




FIGURE 3—ADJUSTING SCREW AND PRESSURE PLATE