



SURFACE VEHICLE STANDARD

J2087

DEC2014

Issued 1991-08
Revised 2014-12

Superseding J2087 OCT2011

Daytime Running Light

RATIONALE

Revisions from comments on Jan. 16, 2014 & May 14, 2014 ballot

REORDERED RATIONALE SECTION - NUMERICAL ORDER

Highlighted in Yellow all changes (ENTIRE DOCUMENT)

Section 2 References

2.2.7 China GB 23255-2009 added as a reference

Corrected spelling of "signalling" and title of UNECE Reg 48

Corrected TC website name

Corrected official name of CMVSS and the agency name to Motor Vehicle Safety

Reordered Table of Contents in Tests and Requirements sections

Added J387, Terminology, as a reference

Section 3 Definitions

3.2 Corrected DRLF definition to agree with J387, Terminology

Sections 5 & 6 Tests & Requirements

5.5 Changed bulb to light source

5.6 changed wording for color

5.7 3m does not apply to DRL provided by headlamps

Added "or a separate lamp" at end after headlamp

Sections 5 and 6 reordered to match order of J575

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2014 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J2087_201412

6.7.2, 6.7.3 – Editorial changes made to improve clarity and understanding, renumbered where required, and corrected typo's

6.7.2

Added "DRLF provided by a" and replaced LED with "Optically Combined with a" Front Position Lamp

6.7.3 a) – Deleted redundant with section 6.7.3.b)

6.7.3 & 6.7.4 Wording corrections - Luminous Intensity

6.9 – Renumbered section and reworded

6.9.4 – added the word "operational" to section heading

6.9.5 – Added section heading "Installation Requirements" and added wording for clarity, "There shall only be one DRLF per vehicle. This shall be made up of one pair of lamps, one on each side of the front of the vehicle, facing to the front."

7., 8., 9. – Renumbered

Changed "parking lamp" to "front position lamp" throughout document

6.7.2 and 6.7.3 amended for clarity

6.7.4 Contains requirements for front turn signals which will remain here until such time that J588 can capture these requirements. Currently there is no reference to the DRL (J2087) in J588. This section is completely rewritten but will not be removed at this time.

Section 7.0

7.1.1, 7.1.2, & 7.1.3 Telltale

7.1.3b amended for clarity

7.2 Operating Guideline to Operation Guideline

7.2.4 Added start-stop engine operation system

7.3.1 Wording - DRL lamps should be spaced as far apart laterally as practicable.

7.4 Removed

Sections 7., 8., & 9. – Renumbered

Changed "parking lamp" to "front position lamp" throughout document including Fig 3 title

All cases of the use of "should" were changed to "shall"

The correction was made to the term "telltale" to agree with J387; Terminology.

FIGURES – remove (delete) footnotes 5 and 6; corrected titles

TABLE OF CONTENTS

1.	SCOPE.....	4
2.	REFERENCES.....	4
2.1	Applicable Documents	4
2.2	Related Publications	4
3.	DEFINITIONS	5
4.	LIGHTING IDENTIFICATION CODE, MARKINGS AND NOTICES.....	5
5.	TESTS.....	6
5.1	Photometry.....	6
5.2	Vibration Test.....	6
5.3	Warpage Test on Devices with Plastic Components	6
5.4	Color Test.....	6
5.5	Moisture Test	6
5.6	Dust Test.....	6
5.7	Corrosion Test.....	6
6.	REQUIREMENTS	6
6.1	Photometry.....	6
6.2	Vibration	7
6.3	Warpage.....	7
6.4	Color.....	7
6.5	Moisture	7
6.6	Dust.....	7
6.7	Corrosion.....	7
6.8	Materials Requirements	10
6.9	System Requirements.....	10
7.	GUIDELINES	11
7.1	Telltale.....	11
7.2	Operation	11
7.3	Installation	12
8.	NOTES.....	12
8.1	Marginal Indicia	12
FIGURE 1	PHOTOMETRIC REQUIREMENTS FOR DEDICATED LAMP PROVIDING DRLF (WITH PROJECTED LUMINOUS LENS AREA OF 200 CM ² OR LESS) MINIMUM LUMINOUS INTENSITY (CD)	8
FIGURE 2	PHOTOMETRIC REQUIREMENTS FOR DEDICATED LAMP PROVIDING DRLF (WITH PROJECTED LUMINOUS LENS AREA GREATER THAN 200 CM ²) MINIMUM LUMINOUS INTENSITY (CD)	9
FIGURE 3	PHOTOMETRIC REQUIREMENTS FOR TURN SIGNAL LAMP OR FRONT POSITION LAMP PROVIDING DRLF MINIMUM LUMINOUS INTENSITY (CD).....	10

1. SCOPE

This SAE Standard provides test procedures, requirements, and guidelines for a daytime running light (DRL) function.

2. REFERENCES

2.1 Applicable Documents

The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications shall apply.

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

SAE J387	Terminology – Motor Vehicle Lighting
SAE J567	Lamp Source Retention System
SAE J575	Test Methods and Equipment for Lighting Devices and Components for Use on Vehicles Less than 2032 mm in Overall Width
SAE J576	Plastic Material or Materials for Use in Optical Parts Such as Lenses and Reflex Reflectors of Motor Vehicle Lighting Devices
SAE J578	Color Specification
SAE J588	Turn Signal Lamps for Use on Motor Vehicles Less than 2032 mm in Overall Width
SAE J759	Lighting Identification Code
SAE J1050	Describing and Measuring the Driver's Field of View
SAE J2560	Forward Lighting Halogen Bulb Performance Requirements for Motor Vehicles

2.2 Related Publications

The following publications are provided for information purposes only and are not a required part of this SAE Technical Report.

2.2.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

SAE Lighting Committee DRL Test Reports, 1974–1989, nine separate reports

2.2.2 CIE Publications

Available from Commission Internationale de L'eclairage, CIE Central Bureau, Kegelgasse 27, A-1030 Wien Austria, Tel: +43-1-714-31-87-0, www.cie.co.at, see also: national organizations of CIE in the case of the USA: United States National Committee of the CIE, c/o Ronald B. Gibbons, Virginia Tech Transportation Institute, 3500 Transportation Research Place, Blacksburg, VA 24061, U.S.A., e-mail: gibbons@vtti.vt.edu, <http://www.cie-usnc.org>

CIE TC4.13 Report Automobile Daytime Running Lights (DRL), Third Draft, July 1990

2.2.3 UMTRI Publications

Available abstracts, <http://www.umich.edu/~industry/complete.html>

2.2.4 United Nations UNECE Publications

Available from United Nations Economic Commission for Europe, Palais des Nations, CH-1211, Geneva 10, Switzerland, Tel: +41-0-22-917-12-34, <http://www.unece.org/trans/main/wp29/wp29regs.html>.

UNECE Regulation No. 48 Uniform Provisions Concerning the Approval of Vehicles with Regard to the Installation of Lighting and Light-Signalling Devices

UNECE Regulation No. 87 Uniform Provisions Concerning the Approval of Daytime Running Lamps for Power-Driven Vehicles

2.2.5 CMVSS Publications

Available from Transport Canada, Motor Vehicle Safety, P.O. Box 8880, Ottawa Post Terminal, Ottawa, Ontario, K1G.3J2 or at www.tc.gc.ca.

Canada Motor Vehicle Safety Standard (CMVSS) 108 Lighting Systems and Retro Reflective Devices

2.2.6 FMVSS Publications

Available from the Superintendent of Documents, U.S. Government Printing Office, 732 North Capitol Street, NW, Washington, DC 20401, <http://www.gpoaccess.gov/cfr/index/html>

CFR Title 49 Part 571.108; Lamps, Reflective Devices and Associated Equipment (FMVSS 108)

2.2.7 China Publications

GB 23255-2009 Photometric Characteristics of Daytime Running Lamps for Motor Vehicles

3. DEFINITIONS

3.1 DAYTIME RUNNING LAMP (DRL)

A lamp providing the daytime running light function.

3.2 DAYTIME RUNNING LIGHT FUNCTION (DRLF)

Steady operating light function that is used to improve conspicuity of a vehicle from the front when the regular headlamps are not required for driving. DRL function can be achieved with low or high beam headlamps, turn signal lamps as well as dedicated lamps.

3.3 DAYTIME RUNNING LIGHT FUNCTION TELLTALE

An indicator that provides a visual signal to advise the driver that only the lamps providing DRLF are operating.

4. LIGHTING IDENTIFICATION CODE, MARKINGS AND NOTICES

Lamps providing DRLF meeting the performance requirements of Section 6 of this document may be identified by the code DRL in accordance with SAE J759.

5. TESTS

SAE J575 is a part of this document. The following tests, from that document, are applicable with the modifications as indicated.

5.1 Photometry

In addition to the test procedures stated in SAE J575, the following applies: Photometric measurements shall be made with the photometer located at least 3 m from the point where the optical axis intersects the outer surface of the DRL lens. This does not apply to DRLF provided by headlamps or a separate lamp.

5.2 Vibration Test

5.3 Warpage Test on Devices with Plastic Components

The light source operation for this test shall be steady burning.

5.4 Color Test

White or Yellow as specified in SAE J578

5.5 Moisture Test

5.6 Dust Test

5.7 Corrosion Test

6. REQUIREMENTS

Performance Requirements

A DRL, when tested in accordance with the test procedures specified in Section 5, shall meet the following requirements:

6.1 Photometry

Shall meet requirements as tested per SAE J575 to the following lamp function types:

6.1.1 Dedicated DRL

The device under test shall be designed to conform to the light intensity distribution (candela) values shown in Figure 1 or Figure 2, Photometric Requirements for Dedicated Lamp Providing DRLF, when tested in accordance with 5.7.

6.1.2 DRLF provided by a Turn Signal or Optically Combined with a Front Position Lamp

The device under test shall be designed to conform when operated at 2.5 times light intensity distribution (candelas) value of the base front turn signal, or shall be designed to conform to the light intensity distribution (candela) values as shown in Figure 3 when tested in accordance with 5.7.

6.1.3 Headlamp Beam Providing the DRLF

A headlamp providing daytime running light function shall have:

- a. In the case of low beam headlamps that are designed to conform to SAE J1383, the luminous intensity from the lamp shall be equal to or greater than 40% but less than 100% of its designed photometric intensity values when tested at 1.5D-2R in accordance with SAE J575 or
- b. In the case of high beam headlamps that are designed to conform to SAE J1383 the luminous intensity shall be greater than 2000 cd but less than 7000 cd at the H-V test point when tested in accordance with SAE J575.

6.1.4 DRL Function Location With Respect to Other Lamps

If a DRL is located such that its lighted edge is within 100 mm of the optical center of a front turn signal lamp, or within 40mm of lighted edge of the front turn signal lamp, it must be extinguished or its luminous intensity reduced to a maximum of 250 cd or less at the H-V axis of the DRL during the turn signal operation. The only exception is when the turn signal is already a 2.5 times turn signal.

6.2 Vibration

SAE J575.

6.3 Warpage

SAE J575.

6.4 Color

SAE J578. The color of the light from a DRL shall be white or yellow as specified in SAE J578.

6.5 Moisture

SAE J575.


6.6 Dust

SAE J575.

6.7 Corrosion


SAE J575.

SAENORM.COM : Click to view the full PDF of j2087_201412



1. The maximum luminous intensity shall be 2500 cd within the photometric pattern.
2. The Measured value at each test point shall not be less than 60% of the required minimum value shown for that individual test point location.
3. The sum of the luminous intensity measurements at each test point within a zone shall not be less than the zone total shown. The luminous intensity measurements at each discrete test point shown within the corresponding zone are the values used to calculate the specified zone total.
4. The listed maximum cd shall not be exceeded over any area larger than that generated by a 0.5 degree radius within the solid angle defined by the test points.

FIGURE 1 – PHOTOMETRIC REQUIREMENTS FOR DEDICATED LAMP PROVIDING DRLF
(with projected luminous lens area of 200 cm² or less)
Minimum Luminous Intensity (cd)



1. The maximum luminous intensity shall be 2500 cd within the photometric pattern.
2. The Measured value at each test point shall not be less than 60% of the required minimum value shown for that individual test point location.
3. The sum of the luminous intensity measurements at each test point within a zone shall not be less than the zone total shown. The luminous intensity measurements at each discrete test point shown within the corresponding zone are the values used to calculate the specified zone total.
4. The listed maximum cd shall not be exceeded over any area larger than that generated by a 0.5 degree radius within the solid angle defined by the test points.

FIGURE 2 – PHOTOMETRIC REQUIREMENTS FOR DEDICATED LAMP PROVIDING DRLF
(with projected luminous lens area greater than 200 cm²)
Minimum Luminous Intensity (cd)