

# SURFACE VEHICLE RECOMMENDED PRACTICE

**SAE** J2200

REAF.  
NOV2001

Issued 1991-01  
Reaffirmed 2001-11

Superseding J2200 APR1995

## Passenger Car and Light Truck Axles

1. **Scope**—This SAE Recommended Practice is intended to outline basic nomenclature for axle designs in common use for automotive drives. Over a period of years, there have been many different designs; however, for the purpose of this report, only the most common designs have been selected and only their general construction is illustrated to show the nomenclature of the various parts.
2. **References**—There are no referenced publications specified herein.
3. **Definitions**
  - 3.1 **Unitized Carrier Housing Construction**—This construction is one in which the housing that supports the ring gear, bearings, and differential case also supports the vehicle load carrying members. See Figure 1.
  - 3.2 **Separable Carrier Housing Construction**—This construction is one in which the carrier that supports the ring gear, bearings, and differential case is separable from the housing that supports the vehicle loads. See Figure 2.
  - 3.3 **Overhung Mounted Drive Pinion**—This construction is one in which the drive pinion teeth are located outside of the span of the bearings. The overhung mounted pinion is illustrated with either Figure 1 or 2.
  - 3.4 **Straddle Mounted Drive Pinion**—This construction is one in which the pinion teeth are located between bearings. The straddle mounted pinion is illustrated in Figure 3.
  - 3.5 **Differential Pinions**—Two or more differential pinions are used to apply torque to each differential gear. The configuration can consist of different numbers of pinion gears such as the two-pinion design in Figure 1 or the four-pinion design in Figure 4A. For optional construction, see Figure 4B.
  - 3.6 **Semifloating Axle Shaft**—In this type of construction (semi-floating) the shaft carries vehicle loads as well as torque. Various types of wheel bearings such as ball bearings or roller bearings are used with this construction. The shaft may have an integral or separable flange. See Figure 5.
  - 3.7 **Full-Floating Axle Shaft**—In this type of construction, the axle shaft does not carry vehicle loads. It only transmits torque. The vehicle loads are transmitted through bearings, directly to the axle housing. See Figure 6.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

TO PLACE A DOCUMENT ORDER: +1 (724) 776-4970 FAX: +1 (724) 776-0790  
SAE WEB ADDRESS <http://www.sae.org>




FIGURE 1—UNITIZED CARRIER HOUSING CONSTRUCTION




FIGURE 2—SEPARABLE CARRIER HOUSING CONSTRUCTION




FIGURE 3—STRADDLE MOUNTED PINION




FIGURE 4A - MULTIPLE PINION DIFFERENTIAL




FIGURE 4B—MULTIPLE PINION DIFFERENTIAL (OPTIONAL CONSTRUCTION)




FIGURE 5—WHEEL END SEMIFLOATING-FLANGED AXLE SHAFT




FIGURE 6—WHEEL END FULL FLOATING AXLE SHAFT