

Submitted for recognition as an American National Standard

CIRCUIT BREAKER—INTERNAL MOUNTED—AUTOMATIC RESET

Foreword—This Document has not changed other than to put it into the new SAE Technical Standards Board Format.

1. Scope

2. References

2.1 Applicable Publication—The following publication forms a part of the specification to the extent specified herein. Unless otherwise indicated the latest revision of SAE publications shall apply.

2.1.1 SAE PUBLICATION—Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

SAE J553—Circuit Breakers

3. Definitions

3.1 Internally Mounted Circuit Breaker—A circuit breaker mounted within an automotive switch or other automotive device for protection against overload of the wiring. In a given application, this same circuit breaker may be designed to protect against overload of the electrically operable devices.

4. Test Procedure

4.1 The circuits containing the internally mounted circuit breakers shall have 3 ft leads connected to their terminals. The wire, size, and mating terminals specified must be the same as the intended application or, if there are a variety of applications, then the minimum wire size with which the circuit breaker will meet the requirements of this recommended practice.

4.2 The circuits containing the internally mounted circuit breakers shall be allowed a 0.20 V drop at rated current, when tested individually, in addition to the voltage drop allowed in the switch or other device specification.

5. Requirements—In a switch or other device with multiple circuit breakers, the following requirements are for testing each circuit breaker individually, with the design load applied to the other circuit breakers:

5.1 Continuously carry 100% of its rated current (as specified by the manufacturer for 1 h at 24 ± 1.6 C (75 ± 3 F)).

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

QUESTIONS REGARDING THIS DOCUMENT: (724) 772-8512 FAX: (724) 776-0243
TO PLACE A DOCUMENT ORDER: (724) 776-4970 FAX: (724) 776-0790
SAE WEB ADDRESS <http://www.sae.org>

SAE J258 Issued JUN71

- 5.2** After a 1 h soak at 51.6 ± 1.6 C (125 ± 3 F) and no load, the circuit breaker shall carry 80% of its rated current for 1 h at that temperature.
- 5.3** Effective current value shall not exceed 140% of its rated current when tested according to procedure as outlined in SAE J553 for Type I.
- 5.4** The circuit breaker must fail safe (open circuit) when tested as outlined in the life test of SAE J553 for 30 min or until destruction.

PREPARED BY THE SAE ELECTRICAL EQUIPMENT COMMITTEE

SAENORM.COM : Click to view the full PDF of J258-197106