

	SURFACE VEHICLE RECOMMENDED PRACTICE		J291 APR2013
		Issued	1972-06
		Stabilized	2013-04
		Superseding J291 JUN1980	
Determination of Brake Fluid Temperature			

RATIONALE

This document has been determined to contain basic and stable technology which is not dynamic in nature.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE Road Test Procedures Standards Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of J291_201304

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2013 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: **Tel:** 877-606-7323 (inside USA and Canada)
 Tel: +1 724-776-4970 (outside USA)
 Fax: 724-776-0790
 Email: CustomerService@sae.org
 http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit**
http://www.sae.org/technical/standards/J291_201304

Foreword—This Reaffirmed Document has been changed only to reflect the new SAE Technical Standards Board Format.

1. Scope—This code provides a test procedure for obtaining and determining extremely high brake fluid temperature encountered in the brake system of a vehicle that is equipped with disc brakes. Vehicles in normal operation may or may not produce brake fluid temperatures that are obtained in this procedure.

1.1 Purpose—To establish a uniform procedure for obtaining and determining a maximum temperature of brake fluid in the automotive braking system of vehicles equipped with disc brakes. This procedure is a uniform means of heating the brakes and the brake fluid and is not a simulation of any other test procedure.

2. References—There are no referenced publications specified herein.

3. Equipment

3.1 Thermocouples

3.2 Line pressure gages, 0–300 psi (0–2.07 MPa) range

3.3 Temperature instrumentation, 650 F (616 K) capability

3.4 Stopwatch

3.5 Calibrated speedometer and odometer

3.6 Ambient temperature thermometer

4. Procedure¹

4.1 Preliminary Preparations

1. Caution—This test may be destructive to the brake system and may affect the handling or stopping ability of the vehicle. It is suggested that the test be conducted by skilled personnel under carefully controlled conditions.