



SURFACE VEHICLE STANDARD

J881™**OCT2021**

Issued 1963-12
Revised 2013-04
Reaffirmed 2021-10

Superseding J881 APR2013

(R) Lifting Crane Sheave and Drum Sizes

RATIONALE

SAE J881 has been reaffirmed to comply with the SAE Five-Year Review policy.

1. SCOPE

This SAE Standard covers minimum dimensional relationship for sheaves, drums, and wire rope for mobile, construction type lift cranes.

2. REFERENCES

There are no referenced publications specified herein.

3. REQUIREMENTS

TABLE 1

Use	Minimum Ratio, PD/RD
Load hoisting sheaves, on boom	18.0:1
Load hoisting sheaves, in traveling blocks	16.0:1
Load hoisting drum	18.0:1
Boom hoisting sheaves	15.0:1
Boom hoisting drum	15.0:1

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2021 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

For more information on this standard, visit
https://www.sae.org/standards/content/J881_202110