



A Product of the
Cooperative Engineering Program

SAE J98 MAY86

Safety for Industrial Wheeled Equipment

SAE Recommended Practice
Reaffirmed May 1986

SAENORM.COM : Click to view the full PDF of j98 - 198605

**S. A. E.
LIBRARY**

Submitted for Recognition as
an American National Standard



*This standard is indexed
in the Standards Search Database*

SAENORM.COM : Click to view the full PDF of j98_198605

No part of this publication may be reproduced in any form,
in an electronic retrieval system or otherwise, without the
prior written permission of the publisher.

Copyright 1986 Society of Automotive Engineers, Inc.

J98 MAY86

RATIONALE:

This SAE Recommended Practice is currently under revision by Subcommittee 25, General Purpose Tractors (Industrial) of the Off-Road Machinery Technical Committee.

RELATIONSHIP OF SAE STANDARD TO ISO STANDARD:

Not applicable.

REFERENCE SECTION:

SAE J38, Lift Arm Support Device for Loaders

SAE J99, Lighting and Marking of Industrial Equipment on Highways

SAE J115, Safety Signs

SAE J153, Safety Considerations for the Operator

SAE J185, Access Systems for Off-Road Machines

SAE J298, Universal Symbols for Operator Controls on Industrial Equipment

SAE J674, Safety Glazing Materials--Motor Vehicles

SAE J718, 540-RPM Power Take-Off for Farm Tractors (Cancelled 1978-See J1170)

SAE J719, 1000-RPM Power Take-Off for Farm Tractors (Cancelled 1978-See J1170)

SAE J721, Operating Requirements for Tractors and Power Take-Off Driven Implements

SAE J1040, Performance Criteria for Rollover Protective Structures (ROPS) for Construction, Earthmoving, Forestry, and Mining Machines

APPLICATION:

This SAE Recommended Practice is intended for use as a guide for manufacturers and users of industrial wheeled equipment to improve the degree of personal safety for operators and others during normal operation and servicing. Avoidance of accidents also depends upon the care exercised by such persons. (See SAE J153.) Inclusion of this practice in state, federal, or any laws or regulations where flexibility of revision is lacking is discouraged.

COMMITTEE COMPOSITION:

DEVELOPED BY SUBCOMMITTEE 25, GENERAL PURPOSE TRACTORS (INDUSTRIAL):

G. A. Stangl, Charles Machine Works, Inc., Perry, OK - Chairman
R. L. Sierk, New Holland Inc., New Holland, PA - Vice Chairman
O. J. Loraas, Melroe Co., Gwinner, ND
E. McCanse, Hesston Corporation, Oregon, IL
R. D. Mickelson, Tenneco Corp., Burlington, IA

DEVELOPED BY SUBCOMMITTEE 25, GENERAL PURPOSE TRACTORS (INDUSTRIAL) (Cont'd.):

H. C. Powers, Caterpillar Tractor Co., Peoria, IL
G. W. Tindall, Deere & Co., Dubuque, IA

SPONSORED BY THE SAE OFF-ROAD MACHINERY TECHNICAL COMMITTEE:

W. L. Black, Clark Michigan Co., Buchanan, MI - Chairman
G. C. Randall, Ford Motor Co., Troy, MI - Vice Chairman
G. R. Bailey, Bailey Marketing Inc., Crystal Lake, IL
W. F. Busbey, Caterpillar Tractor Co., Decatur, IL
D. G. Castine, Trojan Industries, Inc., Batavia, NY
J. B. Codlin, Springfield, IL
C. T. Crawshaw, Aurora, IL
W. L. Daniels Sr., B. F. Goodrich Co., Bloomington, IN
D. W. Driscoll, Cummins Engine Co., Inc., Columbus, IN
G. W. Dudley, Caterpillar Tractor Co., Peoria, IL
F. A. Green, GMC, La Grange, IL
W. C. Jackson, Evans, Charles & Associates, Inc., Las Cruces, NM
R. B. Janvrin, Fluid Controls Inc., Easley, SC
A. D. Lewis, Sparta, NJ
L. R. McLean, Ford Motor Co., Troy, MI
L. E. Miller, Davenport, IA
M. E. Moore, Caterpillar Tractor Co., Peoria, IL
R. J. Nelissen, John Deere Dubuque Works, Dubuque, IA
D. Oldenburg, Caterpillar Tractor Co., Aurora, IL
J. E. Page, Harnischfeger Corporation, Escanaba, MI
J. T. Parrett, St. Joseph, MI
P. D. Redenbarger, Flotec Inc., Indianapolis, IN
G. H. Ritterbusch, Caterpillar Tractor Co., Peoria, IL
R. G. Rumpf, Dresser Industries, Peoria, IL
G. A. Stangl, Charles Machine Works, Inc., Perry, OK
D. R. Thomas, Dresser Industries Inc., Peoria, IL

OFF-HIGHWAY MACHINERY PRACTICE

Submitted for recognition as an American National Standard

SAE J98

Issued May 1973
Reaffirmed May 1986

Reaffirms J98 DEC80

SAFETY FOR INDUSTRIAL WHEELED EQUIPMENT

1. **PURPOSE:** This SAE Recommended Practice is intended to be used as a guide for manufacturers and users of industrial wheeled equipment to improve the degree of personal safety for operators and others during normal operation and servicing. Avoidance of accidents also depends upon the care exercised by such persons. (See SAE J153.) Inclusion of this practice in state, federal, or any laws or regulations where flexibility of revision is lacking is discouraged.
2. **DEFINITIONS:**
 - 2.1 **Industrial wheeled equipment** is defined as that class of tractors and associated equipment used in operations such as landscaping, construction services, loading, digging, grounds keeping, and highway maintenance.
 - 2.2 **Propelling machines** are tractors or self-propelled units.
 - 2.3 **Towed, semi-mounted, and mounted equipment** are equipment used in conjunction with propelling machines as defined in paragraph 2.2.
 - 2.4 **A highway** is the entire width between the boundary lines of every way publicly maintained when any part thereof is open to the use of the public for purposes of vehicular travel. (Uniform Vehicle Code published by National Committee on Uniform Traffic Laws and Ordinances.)
3. **SERVICE:**
 - 3.1 **Servicing or adjusting** shall be done with the engine stopped, unless specific instructions to perform certain operations with the engine running are provided with the equipment.
 - 3.2 **Access** shall be provided to the areas requiring regular servicing, adjusting, or inspecting.

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

4. OPERATOR CONTROLS:

- 4.1 Location and movement of operator controls shall be in accordance with SAE J297.
- 4.2 Controls should be identified. If symbols are used, they shall be in accordance with SAE J298.
- 4.3 Foot pedals shall be of adequate size, spacing, and appropriate configuration, and shall have either slip-resistant surfaces or other means of minimizing the possibility of operator's foot slipping off the pedals.
- 4.4 Hand controls shall be of appropriate configuration and size to permit an adequate grasp and hand clearance.

5. OPERATING AND SERVICING POSITIONS:

- 5.1 All propelling machines and equipment shall be equipped with access systems in accordance with SAE J185.
- 5.2 If the mounting steps or ladder and the hand holds of the propelling machine are made inaccessible by installation of integrally mounted equipment, similar facilities for steps and hand holds shall be provided on the equipment.
- 5.3 A slip-resistant means shall be provided on the operator's platform to minimize the possibility of feet slipping off the platform.
- 5.4 Glazing material, such as glass or plastic used in cabs, shall be of a type and quality that minimizes the risk of injury due to fragmentation when fractured in accordance with SAE J674.
- 5.5 If the operation of the equipment or machine requires a second person on either the propelling machine or the equipment, a suitable position shall be provided which conforms to paragraph 5. Instructions shall discourage any other person from riding on either the equipment or the propelling machine.

6. POWER TAKE-OFF:

- 6.1 The power take-off and power take-off drive lines shall conform to the safety provisions of SAE J718, SAE J719, and SAE J721.
- 6.2 Tractors capable of driving the 540 rpm rear power take-off shaft in excess of 600 rpm or the 1000 rpm rear power take-off in excess of 1100 rpm or the auxiliary power take-off in excess of 1100 rpm shall be equipped with an instrument which will indicate when the PTO is operating at the normal operating speed.
- 6.3 The tractor shall be equipped with means to prevent the operator from inadvertently operating the power take-off in excess of 630 rpm for the 540 rpm shaft or 1150 rpm for the 1000 rpm shaft.

- 6.4 The tractor shall be equipped with a master shield on the rear power take-off (Fig. 1). The master shield shall have sufficient strength to support the weight of the operator without taking a permanent set.
- 6.4.1 Provisions shall be made on the tractor to properly shield the auxiliary power take-off shaft when it is connected to a drive assembly.
- 6.5 The rear and the auxiliary power take-off shafts shall be covered at all times, either by a master shield or other protective means when not connected to a drive assembly.
- 6.6 Both towed and integral-type power take-off driven equipment shall be equipped with adequate shielding for that portion of the power line that is furnished as a part of the driven equipment. This shielding shall prevent the operator from coming in contact with positively driven rotating members of the power line. The shield for the power line between the driven equipment and tractor rear power take-off shall be integral with and journaled on the rotating member. Where integral power take-off driven equipment are of a design requiring removal of the tractor master shield, such driven equipment shall also include adequate protection for that portion of the tractor power shaft which protrudes from the tractor.
- 6.7 Appropriate signs shall be provided at prominent locations on the tractor and the power driven equipment specifying:
- 6.7.1 The normal operating speed of the power take-off shaft (540 or 1000 rpm).
- 6.7.2 The power line safety shields are to be kept in place.
- 6.8 The information specified in paragraphs 6.7.1 and 6.7.2 shall also be shown in the instruction manual.
7. TRACTOR ROLLOVER PROTECTION: Rollover protection (ROPS) shall conform to SAE J1040.
8. SHIELDS OR GUARDS:
- 8.1 Traction Elements: All propelling machines shall be provided with fenders or guards to minimize the possibility of the operator or observer when in the normal position from contacting moving traction elements, unless the propelling machine is fitted with equipment or other means of accomplishing this purpose.
- 8.2 Engine Components: Provision shall be made to minimize the possibility of personal contact with rotating components when the engine is running.
- 8.3 Heat Protection: A guard or shield shall be provided to minimize the possibility of inadvertent contact during normal operation or servicing with any exposed elements which may cause burns.

- 8.4 Power Drives on Propelling Machines and Equipment: The acute entry angles¹ of exposed gears, belts, and chain drives and idlers shall be covered by shields, rods, mesh, or other portions of the machine to minimize the possibility of inadvertent contact.
- 8.5 Constant running drives, or drives that rotate when the engine is running with all clutches disengaged, shall have the outside face of pulleys, sheaves, sprockets, and gears, plus the sides at acute entry angles covered by a shield.
- 8.6 Projections, such as exposed bolts, keys or set screws on sprockets, sheaves or pulleys, shall be shielded unless covered by other portions of the equipment.
- 8.7 Revolving shafts shall be shielded unless covered by other components.
- 8.8 Ground drives shall be shielded in accordance with paragraphs 8.4, 8.6, and 8.7 if personnel are exposed to them while the drivers are in motion.
- 8.9 Functional components, such as cutterbars, flail rotors, mixing augers, conveying augers, rotary tillers, and similar units which must be exposed for proper function shall be shielded to a degree consistent with the intended function of the component.
- 8.10 Access doors and shields, which present the risk of injury from functional components when not in place, shall not be readily detached from the machine.
- 8.11 Access doors and shields for functional components which continue to rotate after the power is disengaged and present the risk of injury shall have a suitable warning provided in the immediate area.
9. LIFTED UNITS: A means shall be provided to protect against inadvertent dropping of lifted units on propelling machines or equipment which must be in raised position for normal servicing or adjusting. (For front-end loaders, see SAE J38.)
10. TRAVEL ON HIGHWAYS:
- 10.1 Lighting and marking of propelling machines and equipment shall conform to SAE J99.
- 10.1.1 The operator's manual for the unit shall instruct the user to operate the flashing warning light whenever the propelling machine is on a highway except when such use is prohibited law.
- 10.2 Hitch pins and other hitching devices shall be provided with a retainer to prevent accidental unhitching.
- 10.3 Appurtenances shall have means for securing them to the main unit.

¹Acute entry angle is the mesh point of gears or the run-on point where a belt or chain contacts a sheave, sprocket, or idler.