

REV.
A

MA2105

FEDERAL SUPPLY CLASS
4720

RATIONALE

MA2105A HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.




FIGURE 1

TABLE 1

HOSE ASSY PART NUMBER	HOSE ASSY SIZE (DN) ¹	THREAD T PER MA1370 4H 5H	A ₁ MAX MM	A ₂ MAX MM	B GAGE DIA BASIC	C MIN DIA THRU	D ₁		D ₂		E ENVELOPE DIA MM	F HEX (REF) MM	R RAD (REF) MM
							MIN MM	MAX MM	MIN MM	MAX MM			
MA2105E	DN06	MJ12X1.25	41.2	37.9	7.5	3.35	12.5	15.5	21.1	27.4	22.9	14	6.4
MA2105G	DN08	MJ14X1.5	47.8	43.1	9.5	6.50	13.7	18.5	24.8	31.2	30.5	17	9.5
MA2105H	DN12	MJ18X1.5	53.9	51.7	13.5	8.76	17.0	23.4	31.2	39.1	33.0	22	12.7
MA2105J	DN16	MJ22X1.5	60.5	60.5	17.5	10.92	21.1	27.4	39.6	47.5	38.1	27	15.9
MA2105K	DN20	MJ27X1.5	68.3	69.4	21.5	14.4	21.8	28.2	42.4	52.1	44.2	32	19.0
MA2105M	DN25	MJ33X1.5	81.0	79.0	26.5	19.3	22.9	29.2	46.7	56.4	58.4	41	25.4
MA2105N	DN32	MJ42X2	93.7	92.6	33.5	23.4	23.9	33.5	53.9	65.8	72.4	46	31.8


¹ DN = NOMINAL TUBE OUTSIDE DIAMETER

TABLE 2

HOSE SIZE (DN) NOM	HOSE		21 °C (70 °F)			BALL SIZE MM (SEE NOTE 5)	CORRECTION FACTOR MM (SEE NOTE 2)	
	ID MIN MM	OD MAX MM	OPERATING PRESSURE MAX KPA	PROOF PRESSURE MIN KPA	BURST PRESSURE MIN KPA		45 DEG FITTING	90 DEG FITTING
06	5.5	11.0	13 750	20 650	55 150	3	2.8	0
08	7.0	13.5	12 000	18 000	48 000	6	2.8	0
12	11.0	20.5	9 800	14 500	38 600	8	2.8	0
16	14.0	24.5	8 300	13 400	33 000	10	2.8	0
20	17.5	29.0	7 200	10 700	29 000	14	2.8	0
25	23.0	36.0	5 500	8 300	22 000	18	2.8	0
32	30.0	44.0	3 800	5 700	15 200	22	3.2	0

SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/MA2105A>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3D (SEE NOTE 7)

PROCUREMENT SPECIFICATION: MA2100



AEROSPACE STANDARD

HOSE ASSEMBLY, METAL, MEDIUM PRESSURE,
FLARELESS, WELDED, 45° TO 90°
FITTING ENDS, METRIC

MA2105
SHEET 1 OF 3

REV.
A

TABLE 3

HOSE ASSEMBLY LENGTH	AVAILABLE LENGTH INCREMENT	LENGTH TOLERANCE
UNDER 457 MM	(NOT LESS THAN) 3 MM	± 3 MM
457 TO 914 MM	(NOT LESS THAN) 7 MM	± 7 MM
914 TO 1270 MM	(NOT LESS THAN) 13 MM	± 13 MM
OVER 1270 MM	(NOT LESS THAN) 26 MM	$\pm 1\%$




FIGURE 2

CONSTRUCTION AND PERFORMANCE: THESE HOSE ASSEMBLIES SHALL MEET THE CONSTRUCTION AND PERFORMANCE REQUIREMENTS OF MA2100 (ISO/DIS7314).

OPERATING CHARACTERISTICS: SEE PROCUREMENT SPECIFICATION.

MATERIALS AND FINISH: 321 OR OTHER CORROSION RESISTANT STEEL, PASSIVATED, IN ACCORDANCE WITH THE PROCUREMENT SPECIFICATION.

IDENTIFICATION: SEE MA2100, 3.7

PROCUREMENT SPECIFICATION: MA2100 (ISO/DIS7314)

NOTES:

1. LENGTH "L" IS MEASURED FROM GAGE POINT TO GAGE POINT. SEE TABLE 3 FOR AVAILABLE LENGTH INCREMENTS. IN THE EXAMPLE OF PART NUMBER BELOW, LENGTH "L" IS DEFINED BY A FOUR DIGIT DASH NUMBER DESCRIBING THE HOSE ASSEMBLY LENGTH IN MM.
2. TO CONVERT "GAGE POINT TO GAGE POINT" TO "END TO END" MEASUREMENT, ADD TO "L" THE APPROPRIATE TABLE 2 CORRECTION FACTOR FOR EACH END FITTING.
3. THE HOSE ASSEMBLIES ARE INTENDED FOR USE IN LOW AND MEDIUM PRESSURE PNEUMATIC SYSTEMS UP TO 425 °C WITH SHORT DURATION EXCURSIONS TO 650 °C. MAXIMUM RATED OPERATING PRESSURE IS DEPENDENT ON AMBIENT OPERATING TEMPERATURE AND CAN BE DETERMINED FROM MA2100, TABLE 2.
4. DIMENSIONS IN MM. DIMENSIONING AND TOLERANCING ARE PER ANSI Y14.5M AND UNIT SYMBOLS ARE PER ANSI Y10.19, SAE J916 AND ANSI Z210.1.
5. A TRUE CIRCULAR CROSS SECTION IS NOT REQUIRED THROUGH THE END FITTING. HOWEVER, A BALL OF THE SIZE DIAMETER LISTED IN TABLE 2 SHALL PASS THROUGH THE END FITTING AFTER THE END FITTING IS ATTACHED TO THE HOSE ASSEMBLY.
6. DO NOT USE UNASSIGNED SIZE CODES.

	AEROSPACE STANDARD	MA2105 SHEET 2 OF 3	REV. A
	HOSE ASSEMBLY, METAL, MEDIUM PRESSURE, FLARELESS, WELDED, 45° TO 90° FITTING ENDS, METRIC		