

## RATIONALE

THIS DOCUMENT HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE 5-YEAR REVIEW POLICY.

MA3444





TABLE 1 - DIMENSIONS

| PART NO.  | THREAD T       | XX SPLINE DASH NO. | ØA        | ØB MIN | C MAX | ØD MAX | F    | H +0.0 -0.6 | L MIN | APPROX MASS kg/100 |
|-----------|----------------|--------------------|-----------|--------|-------|--------|------|-------------|-------|--------------------|
| MA3444-05 | MJ5 x 0.8-4H6H | 07                 | 5.5 - 5.8 | 8.3    | 2.6   | 12.4   | 0.13 | 7.5         | 1.3   | 0.222              |
| MA3444-06 | MJ6 x 1-4H5H   | 08                 | 6.5 - 6.8 | 9.8    | 2.8   | 13.8   | 0.15 | 8.6         | 1.4   | 0.302              |
| MA3444-07 | MJ7 x 1-4H5H   | 09                 | 7.5 - 7.8 | 11.3   | 3.0   | 15.2   | 0.18 | 9.6         | 2.0   | 0.356              |
| MA3444-08 | MJ8 x 1-4H5H   | 10                 | 8.5 - 8.8 | 12.8   | 3.2   | 16.7   | 0.20 | 10.9        | 2.7   | 0.469              |

THIRD ANGLE PROJECTION



PREPARED BY SAE COMMITTEE E-25, GENERAL STANDARDS FOR AEROSPACE PROPULSION SYSTEMS

**SAE Aerospace**  
 An SAE International Group

## METRIC AEROSPACE STANDARD

 NUT, SELF LOCKING - SPLINE DRIVE,  
 CAPTIVE WASHER, UNS S66286,  
 SILVER PLATE, MJ THREAD, METRIC

**MA3444**  
 SHEET 1 OF 2

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright 2006 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

 TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)  
 Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)

Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 1990-02 REAFFIRMED 2006-05